

FEATURES

Compaq ProLiant 1200

Compaq ProLiant 1200 6/233

System Unit

Microprocessor	233-MHz Intel Pentium® II processor
Upgradability	N/A
Cache	512-KB second level ECC cache
Expansion Slots	
I/O (Total)	6
PCI	2
Shared PCI/EISA	4
RAM	
Standard	32 MB
Maximum	512 MB using buffered EDO ECC DIMMS

Network Interface Controllers

Netelligent 10/100 TX UTP Controller (embedded)	Standard
Netelligent 100 FDDI PCI SAS Fiber-SC	Optional
Netelligent 100 FDDI PCI SAS Fiber-MIC	Optional
Netelligent 100 FDDI PCI DAS Fiber-SC	Optional
Netelligent 100 FDDI PCI SAS UTP	Optional
Netelligent 100 FDDI PCI DAS UTP	Optional
Netelligent 100 FDDI EISA SAS Fiber-MIC	Optional
Netelligent 100 FDDI EISA DAS Fiber-MIC	Optional
Netelligent 100 FDDI EISA SAS UTP	Optional
Netelligent 100 FDDI EISA DAS UTP	Optional
Netelligent 10T/2 PCI UTP/Coax Controller	Optional
Netelligent 10 T PCI UTP	Optional
Netelligent 16/4 TR PCI IBM UTP/STP	Optional
Netelligent 4/16 TR PCI UTP/STP	Optional
Netelligent Dual 10/100 TX PCI UTP	Optional
NetFlex-3/P	
100 Base-TX Upgrade Module	Optional (for NetFlex-3)
100Base-FX Upgrade Module	Optional (for NetFlex-3)
100VG-AnyLAN Upgrade Module	Optional (for NetFlex-3)
AUI to BNC Transceiver	Optional

Graphics

Integrated 1024 x 768 by 256 color noninterlaced 1 MB Video System	Standard
--	----------

Compaq ProLiant 1200 6/233

Server Management

Compaq Insight Manager	Standard
Integrated Remote Console	Standard
Integrated Management Display	Optional
Automatic Server Recovery-2	Standard
Server Health Logs	Standard
Recovery Server Option	Optional
Compaq Remote Insight Board	Optional

Storage

Diskette Drives	1.44-MB
CD-ROM Drives	
Standard	16X Max ¹ CD-ROM Drive IDE
Optional	IDE or SCSI
Hard Drives ²	
Standard	None
Optional	2.1-GB, 4.3-GB, 9.1-GB, 18.2-GB Pluggable Wide-Ultra SCSI-3 Drives 4.3-GB, 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm Hard Drives
External Storage	
ProLiant Storage System Models/F1 and /F2	Optional
ProLiant Storage System Models/U1 and /U2	
SCSI Storage Expander	Optional
CD-Storage System	
Tower and Rack Models	Optional
Maximum Storage Capacity	
Internal	54.6 GB (3 x 18.2 GB hot plug drives), 81.9 GB Maximum ³
External	1.15 TB = (7 x 18.2-GB) x 9
Tape Drives	
Optional	2/4-GB DAT, 4/8-GB DAT, 4/8-GB SLR, 12/24-GB DAT, TurboDAT AutoLoaders, 15/30-GB DLT, 35/70-GB DLT, DLT Library 15 Cartridge Model 15/30-1, DLT Library 15 Cartridge Models 3570-1 and 3570-2
Controllers	
Standard	Integrated Wide-Ultra SCSI-3
Optional	32-Bit Fast-Wide SCSI-2/E, Wide-Ultra SCSI-3, Dual Channel Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array, SMART-2/E Array

Interfaces

Parallel	1
Serial	2
Pointing Device (mouse)	1
Graphics	1
Keyboard	1
External Wide-Ultra SCSI-3	1

Compaq ProLiant 1200 6/233

Interfaces *(cont'd)*

Network

RJ-45	1
AUI	1
BNC	Optional with an AUI to BNC converter

Monitors

V55 Color	Standard
V75 Color	Standard
V90 Color	Standard
P50 Color	Standard
P75 Color	Standard
P110 Color	Standard
P1610 Color	Standard
TFT450 Flat Panel Color Monitor	Standard
TFT500 Flat Panel Color Monitor	Standard

LCD Displays

Integrated Management Display	Optional
-------------------------------	----------

Redundant Power Supply

Compaq Hot-Pluggable Redundant Power Supply	Optional
---	----------

Keyboard

Keyboard and Mouse	Standard
--------------------	----------

Supported System Software from Compaq

Compaq SmartStart	Standard
Compaq Insight Manager	Standard
Bayan VINES 6.x and 7.x	Optional
Microsoft Windows NT 3.51 and 4.x	Optional
Novell intraNetWare	Optional
Novell intraNetWare for Small Business	Optional
Novell intraNetWare SFT-III	Optional
Novell NetWare 3.20	Optional
Novell NetWare 4.10	Optional
IBM OS/2 2.x	Optional
IBM OS/2 Warp Family of Products	Optional
SCO UnixWare 2.1.x	Optional
Solaris X86 2.5.x and 2.6	Optional

¹ Hard drive specifications may vary slightly depending on vendor.

² For Maximum storage, remove the CD-ROM for an additional 27.3-GB (3 x 9.1-GB drives).

³ Data transfer rate will vary from 150 KB/s to 2400 KB/s.