

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 155, 2.0 T-Spark CAT 1992 to 1997

Type	AR 672.02 DOHC 104kW	
Capacity (cm ³) / number of cylinders	1995 / 4	
Compression ratio / pressure	bar	10.0 / _
Oil pressure	bar	1.5 [5.0]
Oil temperature	°C	90
Valve clearance - inlet	mm	0.38 to 0.45
Valve clearance - exhaust	mm	0.43 to 0.50
Firing order	1-3-4-2	
No 1 cylinder position	F	
Thermostat opening temperature	°C	87±2
Radiator cap pressure	bar	0.98±0.1

Fuel system 155, 2.0 T-Spark CAT 1992 to 1997

Idle speed - manual [auto]	rpm	840±50
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.2
HC @ idle speed [3000 rpm] - see page VI	ppm	≤50
CO ₂ @ idle speed [3000 rpm] - see page VI	%	_
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	Bosch	
Type / ref	Motronic M1.7	
Main jet / needle	_	
Injection pressure	bar	_
Pump pressure	bar	2.8 to 3.2
Octane rating	RON	95[U]

Ignition system 155, 2.0 T-Spark CAT 1992 to 1997

Type	DME Motronic	
Ignition coil	2xBosch	
Primary resistance	ohms	0.50
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	Bosch	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	Clockwise	
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	Computer control N/A
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs	Champion	
Type	C6YCC	
Electrode gap	mm	0.70

Electrical system 155, 2.0 T-Spark CAT 1992 to 1997

Battery	V / CC / RC	12 / 45Ah / 320 / 60Ah
Alternator voltage / full load current / engine rpm	14.0 / 80 / 3000	
Starter motor current / voltage - cranking	A / V	350 / 9.0
- locked	A / V	750 / 4.0

Running gear 155, 2.0 T-Spark CAT 1992 to 1997

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	3.0

Tyres		
Saloon	Size	195/60x14: 195/55x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.2 / 2.0
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0
Camber	-20'±20' U/L	
Castor	+3°30'±20' U/L	
King pin inclination	+11°30'	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+0.5±0.2 U/L
Camber	-1°±15' U/L	


Torque wrench settings 155, 2.0 T-Spark CAT 1992 to 1997

Cylinder head - stage 1	Nm	76 to 84
- stage 2	Nm	Warm engine, then cool
Cylinder head - stage 3	Nm	- 360°
- stage 4	Nm	83 to 91
Big-end bearings	Nm	49 to 54 oiled
Main bearings	Nm	20 + 115°
Clutch cover	Nm	32 to 40
Flywheel [driveplate]	Nm	116 to 129
Front hubs	Nm	356 to 400
Rear hubs	Nm	304 to 336
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	28 to 35 oiled

Capacities 155, 2.0 T-Spark CAT 1992 to 1997

Engine oil & filter	litres	5.0
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	8.3
Fuel tank	litres	63

Notes and Illustrations



1995 cm³, 8V