

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



# Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

## Engine and cooling system 33, 1.3, S'wagon & 4x4 1990 to 1992

Type		307.32 SOHC (63kW)
Capacity (cm <sup>3</sup> ) / number of cylinders		1351 / 4
Compression ratio / pressure	bar	9.5 / 10.3
Oil pressure	bar	1.2 to 2.8
Oil temperature	°C	90
Valve clearance - inlet	mm	0.35 to 0.40
Valve clearance - exhaust	mm	0.45 to 0.50
Firing order		1-3-2-4
No 1 cylinder position		FR
Thermostat opening temperature	°C	84 to 88
Radiator cap pressure	bar	0.9 to 1.1

## Fuel system 33, 1.3, S'wagon & 4x4 1990 to 1992

Idle speed - manual [auto]	rpm	850 to 1000
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	—
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO <sub>2</sub> @ idle speed [3000 rpm] - see page VI	%	—
O <sub>2</sub> @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Weber/Dellorto
Type / ref		W: 2x40IDF82/3. D: DRLA40FD/S
Main jet / needle		W: 122. D: 118
Injection pressure	bar	—
Pump pressure	bar	0.18 to 0.30
Octane rating	RON	95[E 95 RON]

## Ignition system 33, 1.3, S'wagon & 4x4 1990 to 1992

Type		Electronic
Ignition coil		Bosch
Primary resistance	ohms	0.7 to 1.0
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	12.0
Distributor		—
Points gap (air gap)	mm	[0.40 to 0.50]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	8±1 BTDC @ 900 (1st mark)
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	34 BTDC @ 4500 (2nd mark)
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	0 @ 500
	° Crankshaft @ rpm	19 to 24 @ 3000
	° Crankshaft @ rpm	22 to 26 @ 6000
Vacuum range check	mbar	150 to 400
Maximum vacuum advance	° Crankshaft	11 to 15
Spark plugs		Champion
Type		N6YCC
Electrode gap	mm	0.80

## Electrical system 33, 1.3, S'wagon & 4x4 1990 to 1992

Battery	V / CC / RC	12 / 255 / 50Ah
Alternator voltage / full load current / engine rpm		14.0 / 55 / 4000
Starter motor current / voltage - cranking	A / V	300 / 9.0
- locked	A / V	400 / 5.0

## Running gear 33, 1.3, S'wagon & 4x4 1990 to 1992

<b>Brakes -</b>		
Front (min. friction material thickness)	mm	7.0 with backing
Rear (min. friction material thickness)	mm	0.50. Discs: 6.5
<b>Tyres</b>		
Saloon	Size	165/70x13
Estate / Van	Size	165/70x13
Pressure - front / rear - Saloon	bar	1.8 / 1.8
- Estate / Van	bar	2.2 / 1.8
<b>Front suspension / wheel alignment</b>		
Toe-in (+) / Toe-out (-)	mm [°]	-4.0±2.0
Camber		+1°14'±30'
Castor		+2°±30'
King pin inclination		—
<b>Rear suspension / wheel alignment</b>		
Toe-in (+) / Toe-out (-)	mm [°]	[0±25']
Camber		0±25'

## Torque wrench settings 33, 1.3, S'wagon & 4x4 1990 to 1992

Cylinder head - stage 1	Nm	29 oiled
- stage 2	Nm	58
Cylinder head - stage 3	Nm	81 to 87
- stage 4	Nm	81 to 87 <sup>1</sup>
Big-end bearings	Nm	43 to 48
Main bearings	Nm	66 to 73 oiled <sup>2</sup>
Clutch cover	Nm	15 to 23
Flywheel [driveplate]	Nm	94 to 105 oiled
Front hubs	Nm	427 to 472
Rear hubs	Nm	WSM <sup>3</sup>
Wheel nuts / bolts	Nm	88 to 108
Spark plugs	Nm	25 to 34

## Capacities 33, 1.3, S'wagon & 4x4 1990 to 1992

Engine oil & filter	litres	4.0
Gearbox - 4-speed [5-speed]	litres	2.6
Automatic transmission - refill	litres	—
Final drive	litres	4x4 rear: 1.0
Cooling system	litres	7.8
Fuel tank	litres	50. 4x4: 53


## Notes and Illustrations

<sup>1</sup>Warm engine, cool, slacken, oil, and retorque bolts in sequence shown to stage 4. No.7: 20 to 24


<sup>2</sup>Transverse screws: 40 to 49

<sup>3</sup>Disc brakes: 250 to 300


1: Idle speed 2: CO / Mixture




1351 cm<sup>3</sup>



1351 cm<sup>3</sup>



Weber 40 IDF



Dellorto DRLA