

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 100 4x4, 2.0 16V CAT 1992 to 1994

Type		ACE (103 kW) DOHC 16V
Capacity (cm ³) / number of cylinders		1984 / 4
Compression ratio / pressure	bar	10.8 / ≥7.5
Oil pressure	bar	[2.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	87
Radiator cap pressure	bar	1.2 to 1.5

Fuel system 100 4x4, 2.0 16V CAT 1992 to 1994

Idle speed - manual [auto]	rpm	800 to 1000 N/A
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Bosch
Type / ref		KE-Motronic
Main jet / needle		—
Injection pressure	bar	3.7 to 4.8
Pump pressure	bar	6.1 to 6.6
Octane rating	RON	95[U]

Ignition system 100 4x4, 2.0 16V CAT 1992 to 1994

Type		Motronic
Ignition coil		Bosch
Primary resistance	ohms	0.50 to 1.50
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		Bosch
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	6±1 BTDC @ 800 to 1000
V = Vacuum NV = No Vacuum		V
Total ignition advance	° Crankshaft @ rpm	4 to 8 BTDC @ 800 to 1000
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		NGK
Type		BKUR7ET
Electrode gap	mm	0.70 to 0.90

Electrical system 100 4x4, 2.0 16V CAT 1992 to 1994

Battery	V / CC / RC	12 / 50Ah
Alternator voltage / full load current / engine rpm		12.5 to 14.5 / 90 / 2000
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear 100 4x4, 2.0 16V CAT 1992 to 1994

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.5. Disc: 2.0

Tyres		
Saloon	Size	195/65x15: 205/60x15 ¹
Estate / Van	Size	195/65x15: 205/60x15 ¹
Pressure - front / rear - Saloon	bar	1.9 / 1.9 ²
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+15'+5'-10']
Camber		-40'+35'-25'. Sports: -15'
Castor		+55'±40' N/A
King pin inclination		—

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+10'±10']
Camber		-15'±15'

Torque wrench settings 100 4x4, 2.0 16V CAT 1992 to 1994

Cylinder head - stage 1	Nm	40 N
- stage 2	Nm	60
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	30 + 90°
Main bearings	Nm	65
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	30 + 90°
Front hubs	Nm	200 + 90°
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	30

Capacities 100 4x4, 2.0 16V CAT 1992 to 1994


Engine oil & filter	litres	3.0
Gearbox - 4-speed [5-speed]	litres	2.85
Automatic transmission - refill	litres	—
Final drive	litres	1.7
Cooling system	litres	6.5
Fuel tank	litres	80

Notes and Illustrations


¹Also 215/60x15

²215/60x15: 1.8 / 1.8

1: Idle speed 2: CO / Mixture



1984 cm³, 16V



KE-Motronic, ACE