


[Engine & Cooling](#)
[Fuel](#)
[Ignition](#)
[Electrical](#)
[Running gear](#)
[Torque settings](#)
[Capacities](#)
[Notes & Illustrations](#)


Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

[MENU](#)
[HELP](#)

Engine and cooling system M3 (E36) 1993 to 1996

Type	S50/B30 210kW	
Capacity (cm ³) / number of cylinders	2990 / 6	
Compression ratio / pressure	bar	10.8 / ≥10.0
Oil pressure	bar	1.0 to 1.5 [4.0 to 5.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.28 to 0.33
Valve clearance - exhaust	mm	0.28 to 0.33
Firing order	1-5-3-6-2-4	
No 1 cylinder position	TCE	
Thermostat opening temperature	°C	80
Radiator cap pressure	bar	2.0±0.15

Fuel system M3 (E36) 1993 to 1996

Idle speed - manual [auto]	rpm	800±40
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	Bosch	
Type / ref	DME-Motronic	
Main jet / needle	—	
Injection pressure	bar	—
Pump pressure	bar	—
Octane rating	RON	95[U]

Ignition system M3 (E36) 1993 to 1996

Type	Direct electronic	
Ignition coil	—	
Primary resistance	ohms	0.82
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	—	
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	Computer control N/A
Total ignition advance	° Crankshaft @ rpm	Computer control
Centrifugal check.	° Crankshaft @ rpm	Computer control
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs	Bosch	
Type	Y5DDC	
Electrode gap	mm	0.9-0.1

Electrical system M3 (E36) 1993 to 1996

Battery	V / CC / RC	12 / 65Ah
Alternator voltage / full load current / engine rpm	13.5 to 14.2 / 90 / 1500	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear M3 (E36) 1993 to 1996

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0
Tyres		
Saloon	Size	235/40x17
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.5 / 2.5
- Estate / Van	bar	—
Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+10'±5']
Camber	-55'±30'	
Castor	+6°38'±30' (10° lock)	
King pin inclination	+15°21'±30' (10° lock)	
Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+30'±5']
Camber	-1°45'±10'	


Torque wrench settings M3 (E36) 1993 to 1996

Cylinder head - stage 1	Nm	30 N
- stage 2	Nm	+90°
Cylinder head - stage 3	Nm	+90°
- stage 4	Nm	—
Big-end bearings	Nm	20 + 65° N
Main bearings	Nm	20 + 50° N
Clutch cover	Nm	34
Flywheel [driveplate]	Nm	105 N
Front hubs	Nm	290
Rear hubs	Nm	300
Wheel nuts / bolts	Nm	100±10
Spark plugs	Nm	—

Capacities M3 (E36) 1993 to 1996

Engine oil & filter	litres	7.2
Gearbox - 4-speed [5-speed]	litres	1.2
Automatic transmission - refill	litres	—
Final drive	litres	1.7
Cooling system	litres	12.0
Fuel tank	litres	65

Notes and Illustrations



2990 cm³, 24V