

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 520i & Touring 24V (E34) 1990 to 1993

Type		M50/B20 20 6S1 110kW
Capacity (cm ³) / number of cylinders		1990 / 6
Compression ratio / pressure	bar	10.5 / ≥10.0
Oil pressure	bar	2.0 [4.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-5-3-6-2-4
No 1 cylinder position		TBE
Thermostat opening temperature	°C	80
Radiator cap pressure	bar	2.0±0.15

Fuel system 520i & Touring 24V (E34) 1990 to 1993

Idle speed - manual [auto]	rpm	800±40. 9.90 ▶: 700±40 N/A
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	0.7±0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤300
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Bosch
Type / ref		M3.1-Motronic
Main jet / needle		—
Injection pressure	bar	3.0±0.06
Pump pressure	bar	3.5 to 4.0
Octane rating	RON	95[U]

Ignition system 520i & Touring 24V (E34) 1990 to 1993

Type		Direct electronic
Ignition coil		Bosch
Primary resistance	ohms	0.8±0.1
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		Bosch
Points gap (air gap)	mm	[0.30 to 0.70]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	Computer control
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		Bosch/Champion
Type		F03DAR / C9YCC
Electrode gap	mm	0.90-0.10

Electrical system 520i & Touring 24V (E34) 1990 to 1993

Battery	V / CC / RC	12 / 50, 65Ah
Alternator voltage / full load current / engine rpm		13.5 to 14.2 / 80,140 / 1500
Starter motor current / voltage - cranking	A / V	160 / 9.0
- locked	A / V	—

Running gear 520i & Touring 24V (E34) 1990 to 1993

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	195/65x15: 225/60x15
Estate / Van	Size	205/65x15: 225/60x15
Pressure - front / rear - Saloon	bar	2.2 / 2.1
- Estate / Van	bar	2.1 / 2.4

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+18'±5']
Camber		-13'±30'. Sport: -30'±30'
Castor		+8°8'±30'. Sport: +8°26'±30'
King pin inclination		+12°4'±30'. Sport: +12°38'±30'

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+25'±7']. Sport: [+28'±7'] ¹
Camber		-2°20'±30'. Sport: -2°35' ²

Torque wrench settings 520i & Touring 24V (E34) 1990 to 1993

Cylinder head - stage 1	Nm	30 to 32 WSM
- stage 2	Nm	+ 90±3°
Cylinder head - stage 3	Nm	+ 90±3°
- stage 4	Nm	—
Big-end bearings	Nm	23 + 70° N
Main bearings	Nm	22.5±2.5 + 50±3°
Clutch cover	Nm	24. 10.9 hex: 35
Flywheel [driveplate]	Nm	113 to 130 N
Front hubs	Nm	290
Rear hubs	Nm	247.6 ±5%
Wheel nuts / bolts	Nm	100±10
Spark plugs	Nm	30 to 33


Capacities 520i & Touring 24V (E34) 1990 to 1993

Engine oil & filter	litres	5.75
Gearbox - 4-speed [5-speed]	litres	1.25. S5D: 1.00
Automatic transmission - refill	litres	3.0. A5S: 3.3
Final drive	litres	1.7
Cooling system	litres	10.5. A/C: 11.0
Fuel tank	litres	81

Notes and Illustrations

¹Touring Sport: [+29'±7']

²Touring Sport: -2°45'±30'



1990 cm³, 24V