

Engine & Cooling Fuel Ignition Electrical Running gear Torque settings Capacities Notes & Illustrations



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system BX 16i CAT 1990 to 1991

Type		XU5M (BDZ) 65kW
Capacity (cm ³) / number of cylinders		1580 / 4
Compression ratio / pressure	bar	9.26 / _
Oil pressure	bar	[4.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20±0.05
Valve clearance - exhaust	mm	0.40±0.05
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	82
Radiator cap pressure	bar	1.0

Fuel system BX 16i CAT 1990 to 1991

Idle speed - manual [auto]	rpm	800±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤100
CO ₂ @ idle speed [3000 rpm] - see page VI	%	≥10.0
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Bosch
Type / ref		Monopoint
Main jet / needle		_
Injection pressure	bar	_
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system BX 16i CAT 1990 to 1991

Type		Electronic - Hall effect
Ignition coil		BTR 02
Primary resistance	ohms	0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Ducellier/Bosch
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	° Crankshaft @ rpm	10 BTDC @ 700
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	_
Vacuum range check	mbar	_
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Eyquem/Champion
Type		FC58LS / C7YCX
Electrode gap	mm	0.80

Electrical system BX 16i CAT 1990 to 1991

Battery	V / CC / RC	12 / 225 / 45, / 200 / 33
Alternator voltage / full load current / engine rpm		13.5 / 50 / 3650
Starter motor current / voltage - cranking	A / V	220 /
- locked	A / V	350 /

Running gear BX 16i CAT 1990 to 1991

Brakes -		
Front (min. friction material thickness)	mm	_
Rear (min. friction material thickness)	mm	_
Tyres		
Saloon	Size	155x14: 165/70x14
Estate / Van	Size	165/70x14
Pressure - front / rear - Saloon	bar	165x14: 2.0 / 2.0 ¹
- Estate / Van	bar	2.3 / 2.5
Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0 to -3.0
Camber		0±30'
Castor		+2°±35'
King pin inclination		+11°58'
Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0 to +5.0
Camber		-1°±20'

Torque wrench settings BX 16i CAT 1990 to 1991


Cylinder head - stage 1	Nm	60
- stage 2	Nm	Slacken
Cylinder head - stage 3	Nm	20
- stage 4	Nm	+ 300°
Big-end bearings	Nm	50
Main bearings	Nm	53
Clutch cover	Nm	22
Flywheel [driveplate]	Nm	50 LkC
Front hubs	Nm	270
Rear hubs	Nm	270
Wheel nuts / bolts	Nm	80 Alloy: 90
Spark plugs	Nm	25

Capacities BX 16i CAT 1990 to 1991


Engine oil & filter	litres	5.0
Gearbox - 4-speed [5-speed]	litres	1.8
Automatic transmission - refill	litres	2.5
Final drive	litres	WT
Cooling system	litres	6.5
Fuel tank	litres	52 or 66

Notes and Illustrations

¹155x14: 2.2 / 2.2



1580 cm³



1580 cm³