

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system XM V6 1994 to 1997

Type	ZPJ/Z/L3 (UFZ) SOHC 12V 123kW	
Capacity (cm ³) / number of cylinders	2963 / 6	
Compression ratio / pressure	bar	9.5 / _
Oil pressure	bar	[5.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order	1-6-3-5-2-4	
No 1 cylinder position	FEL	
Thermostat opening temperature	°C	78
Radiator cap pressure	bar	1.4

Fuel system XM V6 1994 to 1997

Idle speed - manual [auto]	rpm	750 [800] A/C: 850 ±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤300
CO ₂ @ idle speed [3000 rpm] - see page VI	%	≥11.0
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	_Siemens Bendix	
Type / ref	Fenix 3B	
Main jet / needle	_	
Injection pressure	bar	3.0
Pump pressure	bar	3.0
Octane rating	RON	95[U]

Ignition system XM V6 1994 to 1997

Type	Fenix 3B	
Ignition coil	Bosch	
Primary resistance	ohms	0.5
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	_	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	_	
Ignition timing - basic [static V = Vacuum NV = No Vacuum	° Crankshaft @ rpm	Computer control N/A
Total ignition advance	° Crankshaft @ rpm	Computer control
Centrifugal check.	° Crankshaft @ rpm	Computer control
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs	Eyquem	
Type	RFC58LS3E	
Electrode gap	mm	1.00±0.01 N/A

Electrical system XM V6 1994 to 1997

Battery	V / CC / RC	12 / 300, 400 / _
Alternator voltage / full load current / engine rpm	13.5 / 90 / 3000	
Starter motor current / voltage - cranking	A / V	300 or 430
- locked	A / V	_

Running gear XM V6 1994 to 1997

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	2.0
Tyres		
Saloon	Size	205/60x15: 205/65x15
Estate / Van	Size	205/60x15: 205/65x15
Pressure - front / rear - Saloon	bar	2.4 / 2.2. AT: 2.3 / 1.9
- Estate / Van	bar	2.4 / 2.4. AT: 2.3 / 2.3
Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0 to -3.0
Camber	0'±30' N/A	
Castor	+2°30'±30' N/A	
King pin inclination	+13°15' N/A	
Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+0.5 to 6.5 N/A
Camber	+50'±20' N/A	


Torque wrench settings XM V6 1994 to 1997

Cylinder head - stage 1	Nm	60
- stage 2	Nm	Slacken
Cylinder head - stage 3	Nm	40
- stage 4	Nm	+180°
Big-end bearings	Nm	20 + 75°
Main bearings	Nm	30 + 75°
Clutch cover	Nm	20
Flywheel [driveplate]	Nm	50 LkC
Front hubs	Nm	320
Rear hubs	Nm	275
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	25

Capacities XM V6 1994 to 1997

Engine oil & filter	litres	6.5
Gearbox - 4-speed [5-speed]	litres	1.85
Automatic transmission - refill	litres	2.7
Final drive	litres	WT
Cooling system	litres	11.8
Fuel tank	litres	80

Notes and Illustrations



2963 cm³, 12V