

[Engine & Cooling](#)
[Fuel](#)
[Ignition](#)
[Electrical](#)
[Running gear](#)
[Torque settings](#)
[Capacities](#)
[Notes & Illustrations](#)


Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

[MENU](#)
[HELP](#)

Engine and cooling system Punto 55 1994 to 1997

Type	176 A6.000 SOHC 40kW EC91	
Capacity (cm ³) / number of cylinders	1108 / 4	
Compression ratio / pressure	bar	9.6 / _
Oil pressure	bar	_
Oil temperature	°C	_
Valve clearance - inlet	mm	0.40±0.05
Valve clearance - exhaust	mm	0.50±0.05
Firing order	1-3-4-2	
No 1 cylinder position	TBE	
Thermostat opening temperature	°C	85 to 89
Radiator cap pressure	bar	0.98

Fuel system Punto 55 1994 to 1997

Idle speed - manual [auto]	rpm	850±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.35
HC @ idle speed [3000 rpm] - see page VI	ppm	≤90
CO ₂ @ idle speed [3000 rpm] - see page VI	%	≥13.0
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	_Weber-Marelli	
Type / ref	SPI IAW 06F.SB	
Main jet / needle	_	
Injection pressure	bar	_
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system Punto 55 1994 to 1997

Type	IAW Static	
Ignition coil	Marelli	
Primary resistance	ohms	0.495±0.6
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	_	
Points gap (air gap)	mm	_
Dwell angle	° (%)	N/A
Condenser capacity	µF	_
Rotation	_	
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	Computer control
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs	_/Champion	
Type	RC9YCC	
Electrode gap	mm	0.85 to 0.95

Electrical system Punto 55 1994 to 1997

Battery	V / CC / RC	12 / 150 / 32Ah
Alternator voltage / full load current / engine rpm	14.3 to 14.6 / 65 / _	
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear Punto 55 1994 to 1997

Brakes -		
Front (min. friction material thickness)	mm	1.5
Rear (min. friction material thickness)	mm	1.5

Tyres		
Saloon	Size	155/70x13:165/65x13:165/60x14
Estate / Van	Size	155/70x16: 165/65x13
Pressure - front / rear - Saloon	bar	2.0 / 1.9
- Estate / Van	bar	2.0 / 1.9

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	0±1.0
Camber	-15' ± 30'	
Castor	1°20' ± 30'. PAS: 2°50'±30'	
King pin inclination	_	

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+1.0±2.0
Camber	+15'±30'	


Torque wrench settings Punto 55 1994 to 1997

Cylinder head - stage 1	Nm	30
- stage 2	Nm	+ 90°
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	_
Big-end bearings	Nm	41
Main bearings	Nm	40 + 90°
Clutch cover	Nm	_
Flywheel [driveplate]	Nm	44
Front hubs	Nm	240
Rear hubs	Nm	280
Wheel nuts / bolts	Nm	86
Spark plugs	Nm	27

Capacities Punto 55 1994 to 1997

Engine oil & filter	litres	3.47
Gearbox - 4-speed [5-speed]	litres	2.37
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	4.6
Fuel tank	litres	47

Notes and Illustrations



1108 cm³