


[Engine & Cooling](#)
[Fuel](#)
[Ignition](#)
[Electrical](#)
[Running gear](#)
[Torque settings](#)
[Capacities](#)
[Notes & Illustrations](#)


Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

[MENU](#)
[HELP](#)

Engine and cooling system Ulysse 2.0 1995 to 1997

Type	ZFA220000(RFU) SOHC 89kW	
Capacity (cm ³) / number of cylinders	1998 / 4	
Compression ratio / pressure	bar	9.5 / _
Oil pressure	bar	[4.8]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20±0.05
Valve clearance - exhaust	mm	0.40±0.05
Firing order	1-3-4-2	
No 1 cylinder position	TBE	
Thermostat opening temperature	°C	89
Radiator cap pressure	bar	1.4

Fuel system Ulysse 2.0 1995 to 1997

Idle speed - manual [auto]	rpm	850±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	_
HC @ idle speed [3000 rpm] - see page VI	ppm	_
CO ₂ @ idle speed [3000 rpm] - see page VI	%	≥13.0
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	_Magneti-Marelli	
Type / ref	8P22	
Main jet / needle	_	
Injection pressure	bar	2.5
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system Ulysse 2.0 1995 to 1997

Type	IAW	
Ignition coil	BAE 04-V5	
Primary resistance	ohms	0.64 to 0.96
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	_	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	_	
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	13°±3° @ 850±50
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs	Bosch/Champion	
Type	FR8 LDC / RC7YCC	
Electrode gap	mm	0.80

Electrical system Ulysse 2.0 1995 to 1997

Battery	V / CC / RC	12 / 250 / 50Ah
Alternator voltage / full load current / engine rpm	70/80Ah	
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear Ulysse 2.0 1995 to 1997

Brakes -		
Front (min. friction material thickness)	mm	1.5
Rear (min. friction material thickness)	mm	1.5

Tyres		
Saloon	Size	195/65x15: 205/65x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.3 / 2.3
- Estate / Van	bar	_

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	1.8±1.0
Camber	0°±30'	
Castor	2°35'±30'	
King pin inclination	11°28'±40'	

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	1.4±1.0
Camber	-1°±30'	


Torque wrench settings Ulysse 2.0 1995 to 1997

Cylinder head - stage 1	Nm	Bolts ≤122mm
- stage 2	Nm	35
Cylinder head - stage 3	Nm	70
- stage 4	Nm	+160°
Big-end bearings	Nm	40, slacken, 20 + 70°
Main bearings	Nm	70
Clutch cover	Nm	20
Flywheel [driveplate]	Nm	50
Front hubs	Nm	300
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	100
Spark plugs	Nm	28

Capacities Ulysse 2.0 1995 to 1997

Engine oil & filter	litres	4.9
Gearbox - 4-speed [5-speed]	litres	1.9
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	8.5
Fuel tank	litres	80

Notes and Illustrations



1998 cm³