

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system Galaxy 2.0 1995 to 1997

Type	NSD. DOHC 8V. 84kW. EEC96	
Capacity (cm ³) / number of cylinders	1998 / 4	
Compression ratio / pressure	bar	9.8 / _
Oil pressure	bar	1.6 [3.1 @ 2000]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order	1-3-4-2	
No 1 cylinder position	TCE	
Thermostat opening temperature	°C	_
Radiator cap pressure	bar	_

Fuel system Galaxy 2.0 1995 to 1997

Idle speed - manual [auto]	rpm	875±50
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	_
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	_ Ford	
Type / ref	EEC V SEFI	
Main jet / needle	_	
Injection pressure	bar	_
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system Galaxy 2.0 1995 to 1997

Type	EEC V	
Ignition coil	_	
Primary resistance	ohms	_
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	_	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	_	
Ignition timing - basic [static V = Vacuum NV = No Vacuum	° Crankshaft @ rpm	Computer control N/A
Total ignition advance	° Crankshaft @ rpm	Computer control
Centrifugal check.	° Crankshaft @ rpm	Computer control
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs	Motorcraft	
Type	AGPR22C1	
Electrode gap	mm	1.00

Electrical system Galaxy 2.0 1995 to 1997

Battery	V / CC / RC	_
Alternator voltage / full load current / engine rpm	_	
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear Galaxy 2.0 1995 to 1997

Brakes -		
Front (min. friction material thickness)	mm	7.0
Rear (min. friction material thickness)	mm	7.0

Tyres		
Saloon	Size	_
Estate / Van	Size	195/65x15:205/60x15:215/60x15
Pressure - front / rear - Saloon	bar	_
- Estate / Van	bar	2.6 / 2.4. 205: 2.7 / 2.5 ¹

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+10'±20'
Camber		-20'±45'
Castor		3°20'±40'
King pin inclination		_

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	0±25'
Camber		-20'±30'

Torque wrench settings Galaxy 2.0 1995 to 1997

Cylinder head - stage 1	Nm	40
- stage 2	Nm	55
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	7 then 16 + 90°
Main bearings	Nm	97
Clutch cover	Nm	30
Flywheel [driveplate]	Nm	87
Front hubs	Nm	150 + 90°
Rear hubs	Nm	200
Wheel nuts / bolts	Nm	140
Spark plugs	Nm	18


Capacities Galaxy 2.0 1995 to 1997

Engine oil & filter	litres	4.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	3.5
Final drive	litres	WT. AT: 0.8
Cooling system	litres	8.2. 2 heaters: 10.0 ²
Fuel tank	litres	70

Notes and Illustrations

¹215/60x15: 2.3 / 2.1

²AT: 8.5, 2 heaters: 10.3. Aux. heater: 10.7, AT: 11.0



1998 cm³, DOHC 8V