

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



## Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

### Engine and cooling system SL320 (129.063) 1993 to 1997

Type		104.991 DOHC 24V 170kW
Capacity (cm <sup>3</sup> ) / number of cylinders		3199 / 6
Compression ratio / pressure	bar	10.0 / 13.5 to 15.5
Oil pressure	bar	0.3 [3.0 @ 3000rpm]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-5-3-6-2-4
No 1 cylinder position		F
Thermostat opening temperature	°C	87±2
Radiator cap pressure	bar	1.40±0.10

### Fuel system SL320 (129.063) 1993 to 1997

Idle speed - manual [auto]	rpm	650 to 800
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO <sub>2</sub> @ idle speed [3000 rpm] - see page VI	%	—
O <sub>2</sub> @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		_ Bosch
Type / ref		HFM MPI
Main jet / needle		—
Injection pressure	bar	3.7 to 4.2
Pump pressure	bar	—
Octane rating	RON	95[U]

### Ignition system SL320 (129.063) 1993 to 1997

Type		EZL
Ignition coil		Bosch
Primary resistance	ohms	0.3 to 0.6
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	Battery
Distributor		—
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		—
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control N/A
V = Vacuum NV = No Vacuum		—
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		Bosch/Champion
Type		F8DCO / C10YCC
Electrode gap	mm	0.80

### Electrical system SL320 (129.063) 1993 to 1997

Battery	V / CC / RC	12 / 92Ah
Alternator voltage / full load current / engine rpm		13.0 to 14.5 / 100 / 2000
Starter motor current / voltage - cranking	A / V	95/11.5
- locked	A / V	—

### Running gear SL320 (129.063) 1993 to 1997

<b>Brakes -</b>		
Front (min. friction material thickness)	mm	2.5
Rear (min. friction material thickness)	mm	2.5

### Tyres

Saloon	Size	225/55x16
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.2 / 2.5
- Estate / Van	bar	—

### Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+20'±10']
Camber		-50'±10'
Castor		10°27'±30'
King pin inclination		—

### Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+25'±5']
Camber		—


### Torque wrench settings SL320 (129.063) 1993 to 1997

Cylinder head - stage 1	Nm	55
- stage 2	Nm	+ 90°
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	—
Big-end bearings	Nm	30, + 90 to 100°
Main bearings	Nm	55, + 90 to 100°
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	30, + 90 to 100°
Front hubs	Nm	WSM
Rear hubs	Nm	200 to 240
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	20

### Capacities SL320 (129.063) 1993 to 1997

Engine oil & filter	litres	7.5
Gearbox - 4-speed [5-speed]	litres	—
Automatic transmission - refill	litres	6.2
Final drive	litres	1.3
Cooling system	litres	11.0
Fuel tank	litres	80

### Notes and Illustrations



3199 cm<sup>3</sup>, 24V