

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system Serena 2.0i (C23) 1993 to 1997

Type		SR20DE DOHC 16V 93kW
Capacity (cm ³) / number of cylinders		1998 / 4
Compression ratio / pressure	bar	9.5 / ≥10.8
Oil pressure	bar	0.8 [4.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TCE
Thermostat opening temperature	°C	76.5
Radiator cap pressure	bar	0.78 to 0.98

Fuel system Serena 2.0i (C23) 1993 to 1997

Idle speed - manual [auto]	rpm	800±50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Nissan
Type / ref		ECCS MPI
Main jet / needle		—
Injection pressure	bar	2.5
Pump pressure	bar	3.0
Octane rating	RON	95[U]

Ignition system Serena 2.0i (C23) 1993 to 1997

Type		Computerized
Ignition coil		Hanshin SMC-200. Mitsu. F-097
Primary resistance	ohms	1.0
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	12.0
Distributor		Hitachi
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	15±2 BTDC @ 800±50
V = Vacuum NV = No Vacuum		V
Total ignition advance	° Crankshaft @ rpm	Computer control
Centrifugal check.	° Crankshaft @ rpm	—
Vacuum range check	° Crankshaft @ rpm	—
Maximum vacuum advance	° Crankshaft @ rpm	—
Spark plugs		NGK
Type		BKR5EY
Electrode gap	mm	0.80 to 0.90

Electrical system Serena 2.0i (C23) 1993 to 1997

Battery	V / CC / RC	12 / 65Ah
Alternator voltage / full load current / engine rpm		14.1 to 14.7 / 63 / 3000
Starter motor current / voltage - cranking	A / V	78 / 11.5
- locked	A / V	—

Running gear Serena 2.0i (C23) 1993 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	1.5
Tyres		
Saloon	Size	195/70x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.0 / 2.6
- Estate / Van	bar	—
Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+3.1 to 5.1
Camber		-30' to +1° N/A
Castor		+2°5' to 3°35' N/A
King pin inclination		+12°45' to 14°15'
Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	-1.8 to +1.8
Camber		-1°15' to 15'

Torque wrench settings Serena 2.0i (C23) 1993 to 1997

Cylinder head - stage 1	Nm	39
- stage 2	Nm	78, loosen completely
Cylinder head - stage 3	Nm	39±5 + 90 to 100°
- stage 4	Nm	+ 90 to 100°
Big-end bearings	Nm	15 + 60 to 65°
Main bearings	Nm	35 + 45 to 50°
Clutch cover	Nm	22 to 29
Flywheel [driveplate]	Nm	83 to 93
Front hubs	Nm	206 to 284
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	98 to 118
Spark plugs	Nm	20 to 29


Capacities Serena 2.0i (C23) 1993 to 1997

Engine oil & filter	litres	3.9
Gearbox - 4-speed [5-speed]	litres	2.1
Automatic transmission - refill	litres	—
Final drive	litres	1.5
Cooling system	litres	9.3
Fuel tank	litres	60


Notes and Illustrations



1: Idle speed 2: CO / Mixture



1998 cm³



ECCS, 1998 cm³