

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 309, 1.6i CAT 1992 to 1994

Type		XU5M3Z (BDY)
Capacity (cm ³) / number of cylinders		1580 / 4
Compression ratio / pressure	bar	9.26 / _
Oil pressure	bar	1.4 [3.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20
Valve clearance - exhaust	mm	0.40
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	82
Radiator cap pressure	bar	1.0

Fuel system 309, 1.6i CAT 1992 to 1994

Idle speed - manual [auto]	rpm	800±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	_
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Magneti-Marelli
Type / ref		MMFD Monopoint G6
Main jet / needle		_
Injection pressure	bar	0.70 to 0.90
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system 309, 1.6i CAT 1992 to 1994

Type		Static
Ignition coil		2x Bosch. Valeo
Primary resistance	ohms	2x0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		_
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Anticlockwise
Ignition timing - basic [static	° Crankshaft @ rpm	[10 to 12] Computer control
V = Vacuum NV = No Vacuum		_
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Eyquem
Type		RFC52LS
Electrode gap	mm	0.80±0.05

Electrical system 309, 1.6i CAT 1992 to 1994

Battery	V / CC / RC	12 / 210 / 65
Alternator voltage / full load current / engine rpm		13.8 to 14.8 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear 309, 1.6i CAT 1992 to 1994

Brakes -		
Front (min. friction material thickness)	mm	1.0
Rear (min. friction material thickness)	mm	_

Tyres		
Saloon	Size	165/70x13
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	1.9 / 1.8
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+0.5±0.5 PW
Camber		-30'±30'
Castor		+2°±30'
King pin inclination		+10°15'±30'

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.8±0.8 PW
Camber		-50'±30'

Torque wrench settings 309, 1.6i CAT 1992 to 1994


Cylinder head - stage 1	Nm	60
- stage 2	Nm	Slacken
Cylinder head - stage 3	Nm	20
- stage 4	Nm	+ 300°
Big-end bearings	Nm	40 ¹
Main bearings	Nm	49
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	49 LkC
Front hubs	Nm	265
Rear hubs	Nm	215
Wheel nuts / bolts	Nm	85
Spark plugs	Nm	25 to 30

Capacities 309, 1.6i CAT 1992 to 1994

Engine oil & filter	litres	5.0. 93 ▶: 4.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	2.4
Final drive	litres	WT
Cooling system	litres	6.1
Fuel tank	litres	55

Notes and Illustrations

¹Slacken, then 20 + 70°



1580 cm³