

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU **HELP**

Engine and cooling system 405, 1.4 1989 to 1991

Type	TU3A (K1G) (51kW)	
Capacity (cm ³) / number of cylinders	1360 / 4	
Compression ratio / pressure	bar	9.3 / _
Oil pressure	bar	1.5 [4.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20
Valve clearance - exhaust	mm	0.40
Firing order	1-3-4-2	
No 1 cylinder position	FE	
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	1.0

Fuel system 405, 1.4 1989 to 1991

Idle speed - manual [auto]	rpm	750±50
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	0.8 to 1.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	≥10.0
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	Solex	
Type / ref	34 PBISA 17-481	
Main jet / needle	132	
Injection pressure	bar	_
Pump pressure	bar	0.25
Octane rating	RON	97[RA] ¹

Ignition system 405, 1.4 1989 to 1991

Type	Electronic	
Ignition coil	_	
Primary resistance	ohms	0.7
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	_	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	Clockwise	
Ignition timing - basic [static	° Crankshaft @ rpm	8 BTDC @ 750 ¹
V = Vacuum NV = No Vacuum	NV	
Total ignition advance	° Crankshaft @ rpm	C057-D044
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	7 to 11 @ 1000
	° Crankshaft @ rpm	20 to 24 @ 3200
	° Crankshaft @ rpm	31 to 35 @ 5600
Vacuum range check	mbar	160 to 385
Maximum vacuum advance	° Crankshaft	6.5 to 9.5
Spark plugs	Eyquem/Champion	
Type	FC52LS / C9YC	
Electrode gap	mm	0.80

Electrical system 405, 1.4 1989 to 1991

Battery	V / CC / RC	12 / 200 / 33
Alternator voltage / full load current / engine rpm	13.8 to 14.8 / _ / 3000	
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear 405, 1.4 1989 to 1991

Brakes -		
Front (min. friction material thickness)	mm	_
Rear (min. friction material thickness)	mm	_
Tyres		
Saloon	Size	165/70x14: 175/70x14
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.1 / 2.1
- Estate / Van	bar	_

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+1.0±0.5 PW
Camber		0±30'
Castor		+2°25'±30'
King pin inclination		+11°25'±30'

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+2.5±0.8 PW
Camber		-1°20'±30'

Torque wrench settings 405, 1.4 1989 to 1991

Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 240°
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	40
Main bearings	Nm	WSM
Clutch cover	Nm	15
Flywheel [driveplate]	Nm	65 LkC
Front hubs	Nm	265
Rear hubs	Nm	275
Wheel nuts / bolts	Nm	85
Spark plugs	Nm	28


Capacities 405, 1.4 1989 to 1991

Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	6.6
Fuel tank	litres	70


Notes and Illustrations

¹[E 95 RON], -4°


1: Idle speed 2: CO / Mixture




1360 cm³



1360 cm³



Solex PBISA



Solex PBISA