

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 405, 2.0i 16V CAT 1992 to 1995

Type		XU10J4/Z (RFY) 112kW DOHC 16V
Capacity (cm ³) / number of cylinders		1998 / 4
Compression ratio / pressure	bar	10.4 / _
Oil pressure	bar	[2.2 to 5.2]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	89 to 101
Radiator cap pressure	bar	1.4

Fuel system 405, 2.0i 16V CAT 1992 to 1995

Idle speed - manual [auto]	rpm	880±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤300
CO ₂ @ idle speed [3000 rpm] - see page VI	%	≥10.0
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Bosch
Type / ref		MP3.2-Motronic MPI
Main jet / needle		_
Injection pressure	bar	3.0
Pump pressure	bar	2.8 to 3.2
Octane rating	RON	95[U]

Ignition system 405, 2.0i 16V CAT 1992 to 1995

Type		Direct electronic
Ignition coil		4xBAE01 (1 per plug)
Primary resistance	ohms	0.7
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		_
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control
V = Vacuum NV = No Vacuum		_
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Eyquem/Champion
Type		FC62LS3 / C7YCX
Electrode gap	mm	1.20

Electrical system 405, 2.0i 16V CAT 1992 to 1995

Battery	V / CC / RC	(12L1 250)
Alternator voltage / full load current / engine rpm		13.8 to 14.8 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear 405, 2.0i 16V CAT 1992 to 1995

Brakes -		
Front (min. friction material thickness)	mm	_
Rear (min. friction material thickness)	mm	_

Tyres		
Saloon	Size	195/55x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.2 / 2.2
- Estate / Van	bar	_

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+1.0±0.5 PW
Camber		0±30'
Castor		+3°±30'
King pin inclination		+11°30'±30'

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+2.75±0.8 PW
Camber		-1°30'±30'

Torque wrench settings 405, 2.0i 16V CAT 1992 to 1995


Cylinder head - stage 1	Nm	60
- stage 2	Nm	Slacken
Cylinder head - stage 3	Nm	20
- stage 4	Nm	+ 300°
Big-end bearings	Nm	40 ¹
Main bearings	Nm	70
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	50 LkC
Front hubs	Nm	320
Rear hubs	Nm	275
Wheel nuts / bolts	Nm	85
Spark plugs	Nm	27

Capacities 405, 2.0i 16V CAT 1992 to 1995

Engine oil & filter	litres	4.25
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	2.4
Final drive	litres	WT
Cooling system	litres	7.0
Fuel tank	litres	70

Notes and Illustrations

¹Slacken, then 20 + 70°



1998 cm³, 16V