

- Engine & Cooling
- Fuel
- Ignition
- Electrical
- Running gear
- Torque settings
- Capacities
- Notes & Illustrations



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

- MENU
- HELP

Engine and cooling system 1.3 1989 to 1990

Type		4G13 SOHC
Capacity (cm ³) / number of cylinders		1298 / 4
Compression ratio / pressure	bar	9.7 / 14.2
Oil pressure	bar	≥0.76
Oil temperature	°C	-
Valve clearance - inlet	mm	0.15 H
Valve clearance - exhaust	mm	0.25 H
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	0.76 to 1.04

Fuel system 1.3 1989 to 1990

Idle speed - manual [auto]	rpm	800±50
Fast idle speed - manual [auto]	rpm	1500±250
CO @ idle speed [3000 rpm] - see page VI	%	1.5±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	-
O ₂ @ idle speed [3000 rpm] - see page VI	%	-
Carburettor / fuel injection		Aisan
Type / ref		2V 3EU
Main jet / needle		93, 150
Injection pressure	bar	-
Pump pressure	bar	0.19 to 0.26
Octane rating	RON	95[E 95 RON]

Ignition system 1.3 1989 to 1990

Type		Electronic
Ignition coil		Diamond E064
Primary resistance	ohms	1.08 to 1.32
Ballast resistor	ohms	1.22 to 1.49
Voltage - Tmnl 15(+) to earth	V	-
Distributor		Mitsubishi
Points gap (air gap)	mm	-
Dwell angle	° (%)	-
Condenser capacity	µF	-
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	6 BTDC @ 850
V = Vacuum NV = No Vacuum		V
Total ignition advance	° Crankshaft @ rpm	-
Centrifugal check.	° Crankshaft @ rpm	0 @ 1600
Vacuum range check	mbar	132 to 400
Maximum vacuum advance	° Crankshaft	15
Spark plugs		NGK/Champion
Type		BPR6ES / RN9YC
Electrode gap	mm	0.70 to 0.80

Electrical system 1.3 1989 to 1990

Battery	V / CC / RC	12 / 60Ah
Alternator voltage / full load current / engine rpm		13.4 to 14.9 / _ / 2500
Starter motor current / voltage - cranking	A / V	-
- locked	A / V	-

Running gear 1.3 1989 to 1990

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	1.0
Tyres		
Saloon	Size	155x13
Estate / Van	Size	-
Pressure - front / rear - Saloon	bar	1.7 / 1.8
- Estate / Van	bar	-
Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0±1.5
Camber		0±30'
Castor		+1°6'±30'
King pin inclination		-
Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	0
Camber		-40'±35'

Torque wrench settings 1.3 1989 to 1990

Cylinder head - stage 1	Nm	70 to 75 C
- stage 2	Nm	80 to 85 H
Cylinder head - stage 3	Nm	-
- stage 4	Nm	-
Big-end bearings	Nm	32 to 35
Main bearings	Nm	50 to 55
Clutch cover	Nm	15 to 22
Flywheel [driveplate]	Nm	130 to 140
Front hubs	Nm	WSM
Rear hubs	Nm	79 to 98
Wheel nuts / bolts	Nm	80
Spark plugs	Nm	20 to 30


Capacities 1.3 1989 to 1990

Engine oil & filter	litres	3.4
Gearbox - 4-speed [5-speed]	litres	2.1
Automatic transmission - refill	litres	-
Final drive	litres	WT
Cooling system	litres	5.0
Fuel tank	litres	45


Notes and Illustrations




- 1: Idle speed
- 2: CO / Mixture



1298 cm³, 8V



1298 cm³, 8V



Aisan 2V