


[Engine & Cooling](#)
[Fuel](#)
[Ignition](#)
[Electrical](#)
[Running gear](#)
[Torque settings](#)
[Capacities](#)
[Notes & Illustrations](#)


Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

[MENU](#)
[HELP](#)

Engine and cooling system Safrane 2.0i 12V (B542/54E) 1993 to 1994

Type		J7R-7-34 [AT: J7R-7-35] 97kW
Capacity (cm ³) / number of cylinders		1995 / 4
Compression ratio / pressure	bar	9.3 / _
Oil pressure	bar	1.25 [3.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.10 to 0.15
Valve clearance - exhaust	mm	0.20 to 0.25
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	83
Radiator cap pressure	bar	0.8 to 1.2

Fuel system Safrane 2.0i 12V (B542/54E) 1993 to 1994

Idle speed - manual [auto]	rpm	825±50 [775±50] N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3 N/A Ex
HC @ idle speed [3000 rpm] - see page VI	ppm	≤100 Ex
CO ₂ @ idle speed [3000 rpm] - see page VI	%	≥14.5
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Siemens Bendix
Type / ref		MPI
Main jet / needle		_
Injection pressure	bar	2.5±0.2
Pump pressure	bar	3.0±0.2
Octane rating	RON	91[U]

Ignition system Safrane 2.0i 12V (B542/54E) 1993 to 1994

Type		Computerized
Ignition coil		Renix
Primary resistance	ohms	0.4 to 0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		_
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	Computer control N/A
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Eyquem/NGK
Type		FC62LS3 / BCP6ET
Electrode gap	mm	1.20 N/A

Electrical system Safrane 2.0i 12V (B542/54E) 1993 to 1994

Battery	V / CC / RC	12 / _
Alternator voltage / full load current / engine rpm		_
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear Safrane 2.0i 12V (B542/54E) 1993 to 1994

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	6.0 with backing

Tyres		
Saloon	Size	195/60x15: 195/65x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.5 / 2.3
- Estate / Van	bar	_

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	-2.0±1.0
Camber		-27'±30' N/A
Castor		+4°8'±30' N/A
King pin inclination		+8°57'±30' N/A

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+2.0±1.0 N/A
Camber		-55' N/A


Torque wrench settings Safrane 2.0i 12V (B542/54E) 1993 to 1994

Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 80°
Cylinder head - stage 3	Nm	Wait 3 mins.
- stage 4	Nm	+ 80°
Big-end bearings	Nm	45 to 50
Main bearings	Nm	88 to 98
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	55 to 60
Front hubs	Nm	250
Rear hubs	Nm	165
Wheel nuts / bolts	Nm	90. 5 bolt: 100
Spark plugs	Nm	_

Capacities Safrane 2.0i 12V (B542/54E) 1993 to 1994

Engine oil & filter	litres	6.1
Gearbox - 4-speed [5-speed]	litres	2.3 to 2.8
Automatic transmission - refill	litres	4.0
Final drive	litres	WT. AT: 1.5
Cooling system	litres	7.0 to 7.2
Fuel tank	litres	80

Notes and Illustrations



1995 cm³, 12V