


Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system Clio 1.2 (B/C/S572/N) 1991 to 1992

Type	E5F-7-10. B57N: E5F-7-16	
Capacity (cm ³) / number of cylinders	1171 / 4	
Compression ratio / pressure	bar	9.25 / 14.0
Oil pressure	bar	1.0 [3.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.10
Valve clearance - exhaust	mm	0.25
Firing order	1-3-4-2	
No 1 cylinder position	FE	
Thermostat opening temperature	°C	86 to 98
Radiator cap pressure	bar	1.2

Fuel system Clio 1.2 (B/C/S572/N) 1991 to 1992

Idle speed - manual [auto]	rpm	800±50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	Pierburg/Zenith	
Type / ref	32 1B1 717625.21/28/29/30/32	
Main jet / needle	102.5	
Injection pressure	bar	—
Pump pressure	bar	0.17 to 0.33
Octane rating	RON	95[E 95 RON]

Ignition system Clio 1.2 (B/C/S572/N) 1991 to 1992

Type	Electronic	
Ignition coil	Renix	
Primary resistance	ohms	0.4 to 0.8
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	—	
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static	° Crankshaft @ rpm	8±1 BTDC @ 800±50
V = Vacuum NV = No Vacuum	NV	
Total ignition advance	° Crankshaft @ rpm	RE292
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	5 to 10 @ 750
	° Crankshaft @ rpm	6 to 12 @ 1550
	° Crankshaft @ rpm	23 to 28 @ 4050
Vacuum range check	mbar	0 to 300
Maximum vacuum advance	° Crankshaft	≥14. E5F-7-16: ≥10
Spark plugs	NGK	
Type	BCP5ES	
Electrode gap	mm	0.80±0.05

Electrical system Clio 1.2 (B/C/S572/N) 1991 to 1992

Battery	V / CC / RC	—
Alternator voltage / full load current / engine rpm	13.5 to 14.8 / 60, 70 / 4000	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	460 / —

Running gear Clio 1.2 (B/C/S572/N) 1991 to 1992

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	2.5 with backing
Tyres		
Saloon	Size	145/70x13: 155/70x13:145/80x13
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.1 / 2.3 ¹
- Estate / Van	bar	—

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	-1.0±1.0 UL
Camber	-20'±30' N/A	
Castor	+1°55'±30' N/A	
King pin inclination	+10°±30' N/A	

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+0.5 to 2.5 N/A
Camber	-50'±30' N/A	

Torque wrench settings Clio 1.2 (B/C/S572/N) 1991 to 1992

Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 97±2°
Cylinder head - stage 3	Nm	Wait 3 mins. Slacken in turn
- stage 4	Nm	20 + 97±2°
Big-end bearings	Nm	40 to 45
Main bearings	Nm	60 to 65
Clutch cover	Nm	25. M8: 30
Flywheel [driveplate]	Nm	50 to 55
Front hubs	Nm	250
Rear hubs	Nm	160
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	—

Capacities Clio 1.2 (B/C/S572/N) 1991 to 1992


Engine oil & filter	litres	4.0
Gearbox - 4-speed [5-speed]	litres	3.25 [3.4] ²
Automatic transmission - refill	litres	—
Final drive	litres	WT
Cooling system	litres	5.2
Fuel tank	litres	43

Notes and Illustrations


¹145/70x13: 2.4 / 2.4. 145/80x13: 2.1 / 2.1

²JB4: 2.75. JB5: 2.9


1: Idle speed 2: CO / Mixture



1171 cm³



1171 cm³



Pierburg / Zenith 1B1