

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system Extra/Express, 1.0 (F400) 1990 to 1992

Type		C1C-B7-06
Capacity (cm ³) / number of cylinders		956 / 4
Compression ratio / pressure	bar	8.6 / _
Oil pressure	bar	0.7 [3.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.15
Valve clearance - exhaust	mm	0.20
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	83
Radiator cap pressure	bar	0.9

Fuel system Extra/Express, 1.0 (F400) 1990 to 1992

Idle speed - manual [auto]	rpm	700±50
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	1.5±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	_
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Zenith
Type / ref		28 IF V05085
Main jet / needle		90
Injection pressure	bar	_
Pump pressure	bar	0.17 to 0.33
Octane rating	RON	92[E 98 RON]

Ignition system Extra/Express, 1.0 (F400) 1990 to 1992

Type		Contact breaker - CIS
Ignition coil		Ducellier, SEV
Primary resistance	ohms	_
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Ducellier
Points gap (air gap)	mm	0.40
Dwell angle	° (%)	57±3 (63±3)
Condenser capacity	µF	_
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	5±1 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	R342-D83
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	0 @ 1300
	° Crankshaft @ rpm	12 to 14 @ 2500
	° Crankshaft @ rpm	26 to 29 @ 5000
Vacuum range check	mbar	93 to 239
Maximum vacuum advance	° Crankshaft	12 to 16
Spark plugs		AC/Champion
Type		C42CMLS / N281YC
Electrode gap	mm	0.75 to 0.85

Electrical system Extra/Express, 1.0 (F400) 1990 to 1992

Battery	V / CC / RC	12 / 175 / 60
Alternator voltage / full load current / engine rpm		13.5 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	340 to 460 / _

Running gear Extra/Express, 1.0 (F400) 1990 to 1992

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	2.5 with backing

Tyres		
Saloon	Size	_
Estate / Van	Size	145x13: 145/70x13
Pressure - front / rear - Saloon	bar	_
- Estate / Van	bar	2.1 / 2.5

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	-1.0±1.0
Camber		+30'±30' N/A
Castor		+2°±30' N/A
King pin inclination		+12°10'±30' N/A

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	0 to +3.0 N/A
Camber		-50'±30' N/A

Torque wrench settings Extra/Express, 1.0 (F400) 1990 to 1992


Cylinder head - stage 1	Nm	55 to 65
- stage 2	Nm	_
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	35
Main bearings	Nm	55 to 65
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	50
Front hubs	Nm	250
Rear hubs	Nm	160
Wheel nuts / bolts	Nm	80
Spark plugs	Nm	_

Capacities Extra/Express, 1.0 (F400) 1990 to 1992


Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	3.3
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	5.5
Fuel tank	litres	43

Notes and Illustrations


1: Idle speed 2: CO / Mixture



956 cm³



956 cm³



Zenith 28 IF