

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 216, 416 SOHC 16V & CAT 1989 to 1996

Type		D16A7. CAT: A6 [AT: Z2] 83kW
Capacity (cm ³) / number of cylinders		1590 / 4
Compression ratio / pressure	bar	9.1 / _
Oil pressure	bar	1.4 [4.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.17 to 0.22
Valve clearance - exhaust	mm	0.22 to 0.27
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	72 to 76
Radiator cap pressure	bar	0.9 to 1.0

Fuel system 216, 416 SOHC 16V & CAT 1989 to 1996

Idle speed - manual [auto]	rpm	780±50, ECU control
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	0.5+0.5-0.3. CAT: ≤0.1
HC @ idle speed [3000 rpm] - see page VI	ppm	≤300
CO ₂ @ idle speed [3000 rpm] - see page VI	%	_
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Honda
Type / ref		PGM-Fi MPI
Main jet / needle		_
Injection pressure	bar	2.3 to 3.0
Pump pressure	bar	≤4.1
Octane rating	RON	95[E 95 RON] ¹

Ignition system 216, 416 SOHC 16V & CAT 1989 to 1996

Type		Computerized
Ignition coil		Unipart GCL161
Primary resistance	ohms	0.71 to 0.81
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Honda
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	18±2 BTDC @ 780±50
V = Vacuum NV = No Vacuum		V
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Unipart/Champion
Type		XHM279, 281, 283, 285 / RC9YCC
Electrode gap	mm	1.00±0.05

Electrical system 216, 416 SOHC 16V & CAT 1989 to 1996

Battery	V / CC / RC	12 / 360 / 60, 12 / 405 / 70
Alternator voltage / full load current / engine rpm		13.9 to 15.1 / 60 / 2750
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear 216, 416 SOHC 16V & CAT 1989 to 1996

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	2.0. Discs: 3.0

Tyres		
Saloon	Size	175/65x14:185/60x14: 185/55x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.1 / 2.1 ²
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[-10'±15'] U/L
Camber		-20'±10' U/L
Castor		+1°59'±30' U/L
King pin inclination		+12° U/L

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+11'±7.5'] PW U/L
Camber		-50' to +50' U/L

Torque wrench settings 216, 416 SOHC 16V & CAT 1989 to 1996

Cylinder head - stage 1	Nm	30
- stage 2	Nm	65
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	32
Main bearings	Nm	67 oiled
Clutch cover	Nm	26
Flywheel [driveplate]	Nm	120 [75]
Front hubs	Nm	185
Rear hubs	Nm	185
Wheel nuts / bolts	Nm	100
Spark plugs	Nm	18

Capacities 216, 416 SOHC 16V & CAT 1989 to 1996


Engine oil & filter	litres	3.4
Gearbox - 4-speed [5-speed]	litres	1.8
Automatic transmission - refill	litres	2.4
Final drive	litres	WT
Cooling system	litres	5.5
Fuel tank	litres	55

Notes and Illustrations


¹CAT: 91 [U]

²185/55x15: 2.2 / 2.2


1: Idle speed 2: CO / Mixture



1590 cm³, SOHC



PGM-Fi



PGM-Fi