

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 9000 2.3 Ecopower L/P Turbo 1994 to 1997

Type	B234E DOHC 16V Turbo 125kW ¹	
Capacity (cm ³) / number of cylinders	2290 / 4	
Compression ratio / pressure	bar	9.25 / _
Oil pressure	bar	[2.7]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
- exhaust	mm	0: Hyd.
Firing order	1-3-4-2	
No 1 cylinder position	TCE	
Thermostat opening temperature	°C	89±2
Radiator cap pressure	bar	0.8 to 1.2

Fuel system 9000 2.3 Ecopower L/P Turbo 1994 to 1997

Idle speed - manual [auto]	rpm	875
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	_
O ₂ @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	Saab	
Type / ref	Trionic SEFI	
Main jet / needle	_	
Injection pressure	bar	3.0
Pump pressure	bar	3.0
Octane rating	RON	91[U]

Ignition system 9000 2.3 Ecopower L/P Turbo 1994 to 1997

Type	Direct electronic	
Ignition coil	Saab	
Primary resistance	ohms	_
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	_	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	_	
Ignition timing - basic [static V = Vacuum NV = No Vacuum	° Crankshaft @ rpm	Computer control
Total ignition advance	° Crankshaft @ rpm	Computer control
Centrifugal check.	° Crankshaft @ rpm	Computer control
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs	NGK	
Type	BCPR7ES	
Electrode gap	mm	1.00+0.10-0.20

Electrical system 9000 2.3 Ecopower L/P Turbo 1994 to 1997

Battery	V / CC / RC	12 / 60Ah
Alternator voltage / full load current / engine rpm	13.9 to 14.8 / 80 / 2500	
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear 9000 2.3 Ecopower L/P Turbo 1994 to 1997

Brakes -		
Front (min. friction material thickness)	mm	4.0
Rear (min. friction material thickness)	mm	4.0
Tyres		
Saloon	Size	195/65x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.1 / 2.1
- Estate / Van	bar	_

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+1.5±0.5
Camber		-0.65°±0.5°
Castor		+1.65°±0.5°
King pin inclination		+11.3°±0.5°

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+2.5±1.5
Camber		-0.5°±0.25°

Torque wrench settings 9000 2.3 Ecopower L/P Turbo 1994 to 1997


Cylinder head - stage 1	Nm	60
- stage 2	Nm	80
- stage 3	Nm	+90°
- stage 4	Nm	_
Big-end bearings	Nm	48
Main bearings	Nm	110
Clutch cover	Nm	22±2
Flywheel [driveplate]	Nm	80
Front hubs	Nm	280 to 300
Rear hubs	Nm	290±10
Wheel nuts / bolts	Nm	115±10
Spark plugs	Nm	28

Capacities 9000 2.3 Ecopower L/P Turbo 1994 to 1997

Engine oil & filter	litres	5.5
Gearbox - 4-speed [5-speed]	litres	1.8
Automatic transmission - refill	litres	3.0 to 3.5
Final drive	litres	WT
Cooling system	litres	9.0
Fuel tank	litres	66

Notes and Illustrations

¹Light pressure intercooled turbo



2290 cm³