

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system Alhambra 2.0 1996 to 1997

Type		ADY. SOHC 8V. 85kW
Capacity (cm ³) / number of cylinders		1984 / 4
Compression ratio / pressure	bar	10.0 / ≥7.5
Oil pressure	bar	[2.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
- exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	85 to 105
Radiator cap pressure	bar	1.4 to 1.6

Fuel system Alhambra 2.0 1996 to 1997

Idle speed - manual [auto]	rpm	770 to 870 N/A
Fast idle speed - manual [auto]	rpm	2500 to 2800 N/A
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5 [≤0.3]
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	-
O ₂ @ idle speed [3000 rpm] - see page VI	%	-
Carburettor / fuel injection		_Volkswagen
Type / ref		Simos
Main jet / needle		-
Injection pressure	bar	2.5
Pump pressure	bar	3.0
Octane rating	RON	95[U]

Ignition system Alhambra 2.0 1996 to 1997

Type		Simos
Ignition coil		-
Primary resistance	ohms	0.5 to 1.2
Ballast resistor	ohms	-
Voltage - Tmnl 15(+) to earth	V	-
Distributor		-
Points gap (air gap)	mm	-
Dwell angle	° (%)	-
Condenser capacity	µF	-
Rotation		-
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control N/A
V = Vacuum NV = No Vacuum		-
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	-
	° Crankshaft @ rpm	-
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	-
	° Crankshaft @ rpm	-
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	-
Spark plugs		NGK
Type		BKUR6ET
Electrode gap	mm	0.70 to 0.90

Electrical system Alhambra 2.0 1996 to 1997

Battery	V / CC / RC	-
Alternator voltage / full load current / engine rpm		-
Starter motor current / voltage - cranking	A / V	-
- locked	A / V	-

Running gear Alhambra 2.0 1996 to 1997

Brakes -		
Front (min. friction material thickness)	mm	7.0
Rear (min. friction material thickness)	mm	7.0

Tyres

Saloon	Size	-
Estate / Van	Size	195/65x15:205/60x15:215/60x15
Pressure - front / rear - Saloon	bar	-
- Estate / Van	bar	-

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+10' ± 20'
Camber		-20' ± 45'
Castor		3°20' ± 40'
King pin inclination		-

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+10' ± 25' (not Nivomat)
Camber		-20' ± 30' (not Nivomat)


Torque wrench settings Alhambra 2.0 1996 to 1997

Cylinder head - stage 1	Nm	40
- stage 2	Nm	60
- stage 3	Nm	+90°
- stage 4	Nm	+90°
Big-end bearings	Nm	30 +90°
Main bearings	Nm	65 +90°
Clutch cover	Nm	-
Flywheel [driveplate]	Nm	60 +90°
Front hubs	Nm	150 +90°
Rear hubs	Nm	200 N
Wheel nuts / bolts	Nm	140
Spark plugs	Nm	30

Capacities Alhambra 2.0 1996 to 1997

Engine oil & filter	litres	4.7
Gearbox - 4-speed [5-speed]	litres	-
Automatic transmission - refill	litres	-
Final drive	litres	WT
Cooling system	litres	7.0. 2 heat exchangers: 9.0'
Fuel tank	litres	70

Notes and Illustrations

1984 cm³, 8V