

- conduction band (CB) 4, 66–7, 74, 119–21, 129, 144–5, 536
- confidence coefficient 918
- confidence interval 918
- conservation of energy 71
- consumer products 57–9
- control strategies 870–1
- cost break down of solar home system 56
- cost distribution for modules and silicon wafers 223
- cost model 35
- cost of electricity for utility-scale PV plants 990–4
- cost projections 50
- costs 15–19
 - for TFSC 34
 - for very high-efficiency 1000 suns-concentrating systems 38
- of construction of PV central plant 35
- of small professional autonomous photovoltaic systems 55
- of stand-alone PV installation 33
 - see also* economic analysis; system cost
- covalent bonds 183
- crystal defects 217–19
- crystal growth techniques, numerical simulations of 244–51
- crystal imperfections, effect of 182–5
- crystalline silicon 21, 27–8, 176, 230
 - bulk properties 257
 - contacting structures 260
 - contacts 257–8
 - progress and challenges 23–7
 - surfaces 256–9
 - wafer material for 245
- crystalline silicon Cz module 35
- crystalline silicon noncontacted surfaces 258–9
- crystalline silicon photovoltaic modules 291–302, 948–9, 955
 - cell matrix 291–2
 - electrical characteristics 295–7
 - fabrication spread 297
 - field performance 301–2
 - lamination and curing 293
 - layers of the module 292–3
 - lifetime 301
 - local shading and hot spot formation 297–9
 - mismatch losses 297
 - optical properties 300
 - postlamination steps 294
 - qualification tests 301–2
 - special modules 294–5
 - thermal characteristics 295–7
 - with back contact cells 295
- crystalline silicon solar cells 255–91, 948
 - back contact print and dry 275
 - back surface 266
 - back surface passivation 281
 - cell structure 259–60
 - cofiring of metal contacts 275
 - front contact print and dry 274–5
 - front surface 263–6
 - manufacturing process 271–80
 - materials and processing 260–2
 - performance comparison 270
 - process flow 271–6
 - size effects 266–8
 - substrate 260–3
 - substrate thickness 263
 - testing and sorting 275
 - throughput and yield 279–80
 - variations to basic process 280–3
- crystalline silicon technology 40
- crystalline silicon wafer PV technology 28
- crystallization 193–4, 216–17, 219, 223
 - from aluminum melt 194
 - from silicon-melt 194
 - heat flow in 247
 - thermal modeling of 245–7
- Cu₂S/CdS thin-film solar cells 568
- Cu–In–Se system 571–2
- CuIn_{1-x}Ga_xSe₂, complex refractive index 575
- Cu(InGa)Se₂ 21, 27, 29, 31, 35
- Cu(InGa)Se₂ solar cells 567–616
 - absorption of light with different wavelengths 595
 - alternative buffer layers 588–90
 - back contact 580
 - buffer layers 591–2
 - chemical bath deposition (CBD) 585–6
 - coevaporation 580–3
 - commercial development 570
 - composition 571–3
 - critical materials with respect to primary supply 608
 - current loss 594
 - deposition methods 578–84, 587–8
 - device completion 592
 - device operation 592–602
 - efficiency 590, 593
 - electrical properties 574–6
 - environmental concerns 608–9
 - equipment 602–4
 - evolution of device record efficiencies 605
 - future outlook 609–11
 - grain boundaries 576–7
 - interface effects 586–7
 - junction and device formation 584–92