

Highly affordable, ultradense server for edge-of-network and Web-based systems



IBM *e*server xSeries 305



Highlights

- **Affordably-priced server to match your business needs and bottom line**
- **Reliable management features help maximize uptime, no matter where the server is located**
- **Choice of Intel Pentium 4 processors for optimal performance**
- **Flexible configurations let you choose the right solution for your business**

The IBM *e*server® xSeries® 305 is a value-packed, entry-level 1U server for Web and network infrastructures.

Highly affordable

The ultradense, rack-optimized x305 can help ease your IT infrastructure and expenses. It packs a cost-efficient, edge-of-network solution in a 1U, 16.75-inch deep form factor. The x305 offers a range of Intel® Pentium® 4 processors with high-performance 533MHz front-side bus and up to 4GB of DDR memory—allowing you to manage expenses or optimize performance.

Streamlined manageability

The x305 takes advantage of innovative cable management, IBM Advanced Connectivity Technology (ACT), to reduce cabling expense and rack clutter. A new slide-mounting

design also simplifies deployment and service. Industry-leading IBM Director and Remote Deployment Manager software take the hassle out of systems management and server deployment. For remote management, the optional IBM Remote Supervisor Adapter lets you remotely manage the x305 from any connected location. Together, these components work to ease the burden on your IT staff and help you increase productivity.

Flexible designs

The x305 can help match your needs:

- *Support for two IDE or SCSI hard disk drives to match your budget and performance needs*
- *Two 64-bit PCI-X slots for fast I/O performance*
- *Integrated Dual Gigabit Ethernet for high-speed network access*



Get it now

go to **ibm.com/eserver/xseries** or call 1 888 **ShopIBM** to buy direct or to locate an IBM reseller.



© Copyright IBM Corporation 2003

Produced in the USA

December 2003

All Rights Reserved

IBM reserves the right to change specifications or other product information without notice. This publication could include technical inaccuracies or typographical errors.

References herein to IBM products and services do not imply that IBM intends to make them available in other countries. IBM makes no representations or warranties regarding third-party products or services. IBM PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore, this disclaimer may not apply to you.

IBM @server systems are assembled in the U.S., Great Britain, Japan, Australia and Brazil and comprise U.S. and non-U.S. components.

IBM, the IBM logo, the e-business logo, @server and xSeries are trademarks or registered trademarks of IBM Corporation in the United States and/or other countries.

Intel, Pentium, Intel Inside, and the Intel Inside logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Microsoft, Windows, Windows NT and the Windows logo are trademarks of Microsoft Corporation. Other product, company and service names may be trademarks or service marks of others.

¹ GB = 1,000,000,000 bytes when referring to storage capacity. Accessible capacity is less.

² Visit ibm.com/pc/safecomputing periodically for the latest information on safe and effective computing.

Warranty Information: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services.

xSeries 305 at a glance

| | |
|---------------------------------------|--|
| Form Factor | Rack/1U |
| Processor | Intel® Pentium® 4 processor with up to 3.06GHz/533MHz front-side bus |
| Number of processors (std/max) | 1/1 |
| Cache (max) | 512KB L2 |
| Memory (std/max) | 256MB/4GB PC2100 |
| Expansion Slots | 2 PCI-X (133MHz) |
| Disk bays (total/hot-swap) | 2/0 |
| Maximum internal storage | 240GB ¹ IDE or 293.6GB SCSI |
| Network | Dual integrated 10/100/1000 Ethernet |
| Power supply (std/max) | 220W 1/1 |
| Hot-swap components | N/A |
| RAID support | Optional |
| Systems management | Automatic Server Restart, Alert Standard Format, Wake On LAN® standard, IBM Director, ServerGuide, optional Remote Deployment Manager, IBM Remote Supervisor Adapter supported |
| Operating systems supported | Microsoft® Windows® Server 2003, Windows 2000®/Advanced Server, Red Hat Linux or SUSE LINUX, Novell NetWare |
| Limited warranty² | 1-year onsite limited warranty |

For more information:

World Wide Web

| | |
|--------|--|
| U.S. | ibm.com/eserver/xseries |
| Canada | ibm.com/ca/eserver/xseries |

Buy Direct

| | |
|--------|----------------|
| U.S. | 1 888 SHOP IBM |
| Canada | 1 888 SHOP IBM |

Reseller locator and general information

| | |
|--------|----------------|
| U.S. | 1 800 426-4968 |
| Canada | 1 800 426-2255 |

