

New **GLOBE SCOUT** Bandswitching Transmitter Model 65 B



A number of changes have been incorporated to make this transmitter one of the best values you have ever seen. A beautiful compact transmitter completely self-contained, including power supply. Rated: 65 watts CW-55 watts phone. Contains 6146 tube in final. Covers 160 meters through 10 meters with complete bandswitching. Metering circuit provides for metering of final grid, final plate circuits and protection of meter. Switching circuit provides protection for modulation circuits. Selector switch for crystal or external VFO operation. Combination pi-network antenna tuner assembly will work into any antenna impedance from 52 to 1000 ohms. May be used with doublet, folded dipole, beam antenna, or any random length wire (preferably $\frac{1}{4}$ wave length at lowest frequency). Coaxial output provided for antenna. All main operation controls are on front panel. Three stage modulator allows complete modulation of the final. Any high impedance microphone may be used. An ideal transmitter for the Novice or the experienced Ham. Trans-

CHECK THESE FEATURES

- * Bandswitching.
- * TVI Shielded Cabinet.
- * Pi Network - Antenna Tuner.
- * Compact - Only 8" high, 8" deep, and 14" wide.

mitter may be used for mobile work with suitable power supply (auxiliary socket provided. B+ and filament voltages for external VFO available at this socket). Tube lineup: 5U4 rect., 6146 final, 6V6 osc., 6L6 mod., 6C5 speech amp., and 6SJ7 mic. amp. A complete kit including all parts, chassis, panel, power supply, streamlined cabinet, tubes, meter and complete, detailed instructions for kit assembly. Size: 8"Dx14"Wx8"H. Sh. wt. 27 lbs.

1000A020K, (Kit) Net 89.95

Terms: 9.00 Down-8.00 Per Month

1000A020W, (Wired) Net 99.95

Terms: 10.00 Down-8.00 Per Month

Accessories

VFO-See Page 1 for WRL VFO Model 755. Crystals, 160, 80 or 40M (40M used on 10-20). See page 27, Each... 2.88
53A008, JT-30 microphone and stand 9.97
50B025, Johnson 114-300 Key 1.96



New **GLOBE CHIEF** Bandswitching Transmitter Model 90

CHECK THESE FEATURES

- * 90 Watts Maximum Input. 75 Watts for Novice Use.
- * Bandswitching.
- * Pi Network - Antenna Tuner.
- * Safe Grid-Block Keying.

The Globe Chief Transmitter, Model 90, is a new member of the world famous WRL series of transmitters. Designed primarily as a CW transmitter for the Novice, the Globe Chief incorporates several features that make it desirable to any Ham operator regardless of class of license. Completely self-contained in a handsome cabinet finished in gray hammerstone. Ventilating grilles provide adequate ventilation and heat dissipation. The meter and cabinet are fully shielded for TVI reduction. Rated: 90 watts full output all bands; 75 watts for novice use. Contains two 807 tubes in final. Covers 160 through 10 meters with complete bandswitching. Combination pi-network output circuit matches most antennas 50 to 800 ohms. All operating controls on front panel. Safe keying through use of modified blocked-grid system. Voltage across the key limited to less than 75 volts. Provision provided for use with external VFO; speech modula-

tor; antenna change-over relay. Kit contains pre-punched chassis, all wires pre-cut to length and pre-tinned, and all necessary parts and components. Excellent instruction manual provided for assembly and operation. Dimensions: 8" H x 8"D x 14 1/2"W. Sh. wt. 27 lbs.

1000A075K, (Kit) Net 49.95

Terms: 5.00 Down-5.00 Per Month

1000A075W, (Wired) Net 64.95

Terms: 6.50 Down-5.50 Per Month

Accessories

1000A076K, WRL Screen Modulator Kit, Net 13.95
50B025, Johnson 114-300 Key, Net 1.96
54A131, Antenna Change-over relay, Net 3.75
Crystals, see page 27, Net 2.88

PURCHASE ANY EQUIPMENT ON MONTHLY PAYMENT PLAN-SEE PAGE 193