



- NOTES:
1. RESISTANCE VALUES ARE SHOWN IN OHMS UNLESS OTHERWISE NOTED. (K=KILO OHM, M=MEG OHM)
 2. RESISTOR WATTAGES ARE 1/8W UNLESS OTHERWISE NOTED.
 3. CAPACITANCE VALUES ARE INDICATED IN MICRO FARADS UNLESS OTHERWISE NOTED. (P=PICO-MICRO FARAD)
 4. ALL CAPACITORS TEMPERATURE CHARACTERISTICS ARE SL (LESS THAN 1000PF) OR YF (MORE THAN 1000PF) UNLESS OTHERWISE NOTED.
 5. VOLTAGE IN \square SHOWS TX CONDITION.
 6. VOLTAGE IN \square SHOWS RX CONDITION UNDER OPERATION OF EACH FUNCTION.
 7. VOLTAGE IN \square SHOWS TX CONDITION.

PRESIDENT
JIMMY

DESIGN BY	DRAWN BY	WESTON NO.	MODEL NO.
S42.12.2	M.K	UT-317 J	JIMMY
KOMA		TITLE	
CHECK BY	APPRO BY	SCHEMATIC DIAGRAM 1/2	
S42.12.4		E12-2737 1/2	REV. MARK