
TESTPOINT NOTE:
ALL AC VOLTAGES (VAC) ARE RMS.
DC VOLTAGES ARE WITH NO SIGNAL APPLIED.
VOL & TONE @ 10 ALL OTHERS @ 0
212VDC
11VAC
340VDC
0VAC
356VDC
0VAC
224VDC
26 VAC
218VDC
24.5VAC
193VDC
.25Vp-p ripple
400VDC
5Vp-p ripple
0VDC
5VAC p-p
8VDC
17.5VAC
+7VDC
-7VDC
1KHZ SINE WAVE 24mVRMS
ACCESSORY
GUITAR
VOLUME
TREMOT
TONE
INTENSITY
SPEED
REVERB
TREMOLO
FOOTSWICH BREAK-OFF BOARD
8 OHM SPEAKER
BIAS ADJUST NOTE
ADJUST BIAS FOR SLIGHT CROSSOVER NOTCH @ FULL OUTPUT.
LINE CURRENT 384mV BETWEEN .65-.70A
NOTES:
1) THIS UNIT CONTAINS HAZARDOUS VOLTAGE. DISCONNECT POWER AND BE SURE POWER SUPPLY IS DISCHARGED BEFORE TOUCHING INTERNAL PARTS.
2) UNLESS NOTED, RESISTOR VALUES IN OHMS, 1/4W 5% TOL. CAPACITOR VALUES IN MICROFARADS, 50V 10% TOL.
3) VOLTAGES ARE MEASURED WITH 1 MEGOHM OSCILLOSCOPE AND 10 MEGOHM DIGITAL VOLTMETER.
CAUTION
THIS SCHEMATIC IS PROVIDED FOR USE BY QUALIFIED PERSONNEL. TO AVOID RISK OF ELECTRIC SHOCK, REFER SERVICING TO QUALIFIED SERVICE PERSONNEL. DO NOT PERFORM ANY SERVICING BEYOND THAT EXPLAINED IN THE OPERATING INSTRUCTIONS.
LAST DESIGNATOR USED
NOT USED
ADDED "V" VER. AND CONVERTED TO AUTOCAD.
REV TO PCT E970101 & E980380.
R24 WAS WIRE WOUND. CHANGE PER ECO #980279
DESCRIPTION
SIGNATURES:
DRAWN: REM 11/2/98
CHK'D: OK 11/2/98
APP'D: OK 11/2/98
ORIGINAL ISSUED: 11/2/98
PLOT DATE: 10/06/98
PLOT TIME: 10:17:11
FILE NAME: 2771144
REV'D WITH PICTORIAL FOR RADIAL CHANGES PER KIMBER
PROJECT NAME: SJ-12T
DRAWING NAME: SCHEMATIC
DRAWING NO. 07S277-11
REV 4
SCALE: 1:1
SHEET: 1 OF 1
COPYRIGHT SLM ELECTRONICS