



- M6 D2/D10 (RECT.) DIODE
- M7 VR2 (PTH)/T13 HEATSINK
- M8 T9 HEATSINK
- M9 +15V/-15V/+5V/+48V/+12V HEATSINK
- M10 D27 (BRIDGE RECT.) HEATSINK
- M11 T10/VR1 (PTH) HEATSINK

- MIXER HCA2400
- X1 +15V
- X2 -15V
- X3 AGND
- X4 +48V
- X5 +5V
- X6 POS.
- X7 C.GND
- X8 OFF

ALL INFORMATION (INCLUDING DRAWINGS AND DIAGRAMS) CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF BEHRINGER. ADDRESSEES WHOM THE INFORMATION IS CONFIDED TO SHALL MAINTAIN THE INFORMATION IN CONFIDENCE AND SHALL NOT RELEASE IT TO ANY UNAUTHORIZED THIRD PARTIES (EXCEPT UNDER ATTORNEY CLIENT PRIVILEGE OR UNDER APPROPRIATE CONFIDENTIALITY AGREEMENTS). ANY UNAUTHORIZED DISCLOSURE, USE, APPLICATION OR ANY OTHER DEALINGS IN THE INFORMATION SHALL RESULT IN CIVIL AND/OR (WHERE APPLICABLE) CRIMINAL LIABILITIES AND PENALTIES.

REV	CHANGES	DATE	INT	FILE:	DATE	NAME
C	MODIFIED	151205	SASA		2010/04	L.RAMOS
B	MODIFIED	190405	SASA			
A	CREATED	201004	LR			
EV	CHANGES			FILE: sps1000_2		

SPS1000		SHEET 1 OF 1
SCHEMATIC		
MAIN		