



**LAST USED LIST**

Desig.	Ch.1 1-50	Ch.2 51-100	Sys. 101-200
A	2	-	102
C	14	64	122
D	3	53	114
H	-	-	4
JMP	2	4	5
K	1	51	-
L	1	51	-
P	1	51	101
Q	12	62	106
QC	-	-	14
R	34	84	127
T	-	-	101
Z	4	54	105

**LABELS NOT USED**

C	
D	
Q	104
R	28, 29, 30, 80
Z	

- 9 THERMISTOR MUST BE IN CONTACT WITH HEATSINK.
  - 8 CUT THIS TRACE ONLY IF H2 IS USED FOR BRIDGE MONO PHASING.
  - 7 ADJUST P1/P51 FOR 6mV (±0.2mV) DROP ACROSS R109/R110 RESPECTIVELY UNIT WARM, 120 VAC LINE.
  - 6 ADJUST P101 FOR 8.0 Vdc (±0.1 Vdc) AT A102 PIN 2.
  - 5 T1 IS: 15-50098 FOR FX MIXERS.
  - 4. A1, A2, A101, AND A102 ARE MC33078 OP AMPS.
  - 3. ALL RESISTORS IN OHMS.
  - 2. ALL DIODES ARE 1N4003 (EXCEPT AS NOTED).
  - 1. ALL CAPACITORS IN MICROFARADS (EXCEPT AS NOTED).
- NOTES: UNLESS OTHERWISE SPECIFIED**

12340 World Trade Drive  
San Diego, CA 92128  
(619) 487-1600  
FAX 487-6629

**CARVIN**

**1000W STEREO  
POWER MODULE**

DRAWN BY: C. McEUEEN      DATE: 19JUN90

APPROVED:      DATE:

PCB NO: 30-10028      REV: H

ASSY. NO: 80-10028      REV: U

REVISED BY: Craig Hockenberry      DATE: 20APR95