

PHOTOMULTIPLIER TUBE

TYPE : R6357

CUSTOMER : UNIV OF CALIF SAN DIEGO

QUANTITY : 2 pcs.

Serial Number	(1) Cathode Luminous Sens.	(2) Anode Luminous Sens.	(3) Anode Dark Current	(4) R/W	(5) Cathode Blue Sens. Index		
	$\mu$ A/lm	A/lm	nA	$\times 10^{-3}$			
MJ5630	425.0	2500.0	0.97	344.0	12.70		
MJ5634	442.0	1220.0	2.70	362.0	12.30		

NOTES

- (1) (2) (4) (5) Light source : Tungsten filament lamp operated at 2856 K.
- (2) (3) Overall supply voltage : 1000 V
- Voltage distribution : The standard voltage distribution ratio listed in the HAMAMATSU photomultiplier catalog.
- (3) The bulb of the tube is insulated from ground potential.
- (4) The quotient of the red light sensitivity (measured with a Toshiba R-68 red filter) divided by the white light sensitivity.
- (5) Measured with a Corning CS 5-58 blue filter (half stock thickness).

Date: JANUARY 12, 2006

Approved by : *T. Haranoya*

**HAMAMATSU**

HAMAMATSU PHOTONICS K.K., Electron Tube Division  
314-5, Shimokanzo, Iwata City, Shizuoka Pref., 438-0193, Japan, Telephone : (81)0539/62-5248, Fax : (81)0539/62-2205